

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O. & G.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

JUL 28 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

- 1. oil well gas well other
- 2. NAME OF OPERATOR
Amoco Production Co.
- 3. ADDRESS OF OPERATOR
P. O. Box 68 - Hobbs
- 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FWL, Sec. 14
AT TOP PROD. INTERVAL: (Unit F, SE/4, NW/4)
AT TOTAL DEPTH:
- 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- 5. LEASE
NM-16835
- 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
- 7. UNIT AGREEMENT NAME
- 8. FARM OR LEASE NAME
Federal AG Com
- 9. WELL NO.
1
- 10. FIELD OR WILDCAT NAME
Wildcat West Osudo Morrow
- 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
14-20-35
- 12. COUNTY OR PARISH
Lea
- 13. STATE
NM
- 14. API NO.
- 15. ELEVATIONS (SHOW DF, KDB, AND WD)
3695.2 RDB

- | | | | |
|--------------------------|--------------------------|-----------------------|-------------------------------------|
| REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: | |
| TEST WATER SHUT-OFF | <input type="checkbox"/> | | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | | <input checked="" type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | | <input type="checkbox"/> |
- (other) _____

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 7-14-80. Milled cast iron bridge plug from 13250'-13252' and pushed it to 13400'. Ran tubing, packer and tailpipe. Packer set at 11055'. Tailpipe set at 12932'. Perforated 13007'-17' and 13119'- 42' with 4 JSPF. Acidized with 3000 gal. 7 1/2% MS Acid. Currently flow testing.

0+4-NMOCD, H 1-Hou 1-Susp 1-LBG 1-Superior

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bob Davis TITLE Admin. Analyst DATE 7-25-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
JUL 29 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO