

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

P. O. BOX 1980
HOBBS, NEW MEXICO

588246

NM-1366-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Featherstone Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 21, T20S-R35E

12. COUNTY OR PARISH | 13. STATE
Lea | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3716' GR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR
P.O. Box 4500 The Woodlands, Texas 77380

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1980' FNL & 1980' FEL
AT SURFACE: Sec. 21, T20S-R35E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Straight hole


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*
- (other) Set casing

-
-
-
-
-
-
-
-



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-26-81 Installed casing head. Tested to 500#-OK. NU BOP's. Drilling ahead.
thru MD 4036' MW 10.1#.
9-4-81

9-8-81 Drilled to 4421'. Ran & set 10-3/4" at 4421'. Cemented first stage w/1275 sxs Class "C". Displaced cement. MW 9.3#.

9-9-81 Cemented second stage through DV tool at 2491' w/4500 sxs 65-35 Pozmix. Circulated 700 sxs to surface. MW 9.6#.

9-10-81 Installed casing spool. NU & tested BOP's. MD 4425' MW 9.6#.

9-11-81 Tested casing to 1000#-OK. Drilled DV tool & float collar. Tested casing to 1000#-OK. MW 9.6#.

9-12-81 thru 9-18-81 Drilling ahead. MD 7000' MW 8.4#.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. Bannantine TITLE Reg. Group Mgr. DATE September 22, 1981

SEP 30 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

USGS (3), RG