

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE (Other instructions reverse side)

E* re-

Form approved. Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 15906

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Sam H. Snoddy Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, TWP-20-S

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR Ike Lovelady, Inc.

3. ADDRESS OF OPERATOR P.O. Drawer 2666; Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface

660' FNL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3555.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drig. & run 5-1/2" Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/2/82 to 9/3/82 Drilling 8-3/4" hole to 13,480'.

9/4/82 logging open hole, Ran Compensated Neutron Formation Density from 13,470' back to 3550'. Ran Dual Laterlog Micro-SFL from 13,470' back to 5202'.

9/7/82 to 9/8/82 Ran 5-1/2" Csg. 17# & 20# N-80 set @ 13,480' with D.V. tool @ 10,795'. Cement bottom stage W/650 Sks, cir cement on bottom stage. Cement top stage W/500 Sks. Ran temp. survey - top cement 8400'. Tested casing to 1500# @ surface. Released drilling rig.

RECEIVED

SEP 27 1982

OIL & GAS MINERALS MGMT. SERVICE ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Paul J. Sims

TITLE Paul J. Sims, Mgr. of Drig. DATE September 15, 1982

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY

TITLE DATE

ACCEPTED FOR RECORD OCT 7 1982 U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

OCT 8 1982

O.C.S.
HOBBBS OFFICE