

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

CO. 88240

LC - 029512 -B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Teas Yates Unit

8. FARM OR LEASE NAME

Tract # 1

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Teas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 18, Twp 20S, Rg 34E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3614' GR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Water Injection Well

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P.O. Box 806 Eunice, New Mexico 88231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 10' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

☒ SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Run 7" csg & cement

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Resumed drlg @ 7:30 AM 4-14-83 w/8½" bit.
2. Drilled to 2300'. Noranda Corp. took over rig & cored potash from 2300' to 2350'. Resumed drlg w/8½" button bit @ 9:15 AM 4-15-83.
3. Drilled 8½" hole to 3223' @ 9:30 AM 4-17-83.
4. Ran 84 jts (3223') of 7" used 26.40#, S-95, Rg 3, LT&C csg.
5. Cemented w/800 sx Halliburton Lt. cement w/15# salt per sx & 2% CACL. Followed w/200 sx Class "C" Neat cement. Plug down @ 9:45 AM 4-18-83. Circ 135 sx to pit. Released drlg rig @ 12:45 PM 4-18-83.
6. Moved in Pulling Unit & Reverse Rig to drill through Yates zone 4-28-83.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original

SIGNED by: Howard D. [Signature] TITLE Field Foreman

DATE May 4, 1983

(This space for Federal or State office use)

APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY: _____

TITLE _____

DATE _____

ACCEPTED FOR RECORD

PP

AUG 9 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO