

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other Water Injection

2. NAME OF OPERATOR
Anadarko Production Company

3. ADDRESS OF OPERATOR
P.O. Box 806 Eunice, New Mexico 88231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2250' FSL & 975' FWL
AT TOP PROD. INTERVAL: Sec 13, Twp 20S, Rg 33E
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	X	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON (other) <u>New Well, cementing csg.</u>	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE <u>NM 0435</u>	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME <u>Teas Yates Unit</u>	
8. FARM OR LEASE NAME <u>Tract 8</u>	
9. WELL NO. <u>4</u>	
10. FIELD OR WILDCAT NAME <u>Teas</u>	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec 13, Twp 20S, Rg 33E</u>	
12. COUNTY OR PARISH <u>Lea</u>	13. STATE <u>NM</u>
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) <u>3609.9 GR</u>	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilling on cement plug 1:30 A.M. 3-22-83.
2. Drill 8-3/4" hole to about 3225' 10:15 P.M. 3-23-83.
3. Ran 81 jts. of 7" , 23# csg w/csg shoe 3225'. Cemented w/630 sx Halliburton Lt. w/15# salt & 2% CACL, followed w/200 sx Class C Neat. Plug down 8:15 A.M. 3-24-83. Circulated cement.
4. WO Completion Unit.

Subsurface Safety Valve: Manu. and Type

Set: @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Field Foreman DATE April 6, 1983

ACCEPTED FOR RECORD (space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE _____
CONDITIONS OF APPROVAL APR 20 1983