STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we. or Corica Accesses		
DISTRIBUTION		
BANTA FE		
FILE		
U.S.O.S.	Ī	
LAND OFFICE		
OPERATOR	T	

OIL CONSERVATION DIVISION

PISTAIRUTION		O. BOX 2088	Form C-103 Revised 19-1-78
SANTA PE	SANTA FE,	NEW MEXICO 87501	
U.S.O.S.	•	•	Sa. Indicate Type of Lesse
LAND OFFICE		·	State X Fno
OPERATOR			5. State Oli & Gas Lease No.
			A-1212-1
SUNDRY JOO NOT USE THIS FORM FOR PROFUSETION USE "TAPPLICATION	Y NOTICES AND REPORT POSALS TO PRILL OR TO GEEPEN OF ON FOR PERMIT -11 IFORM C-1011	TS ON WELLS PRUGBACK TO A DIFFERENT RESERVOIR. FOR SUCH PROPOSALB.	
1.			7. Unit Agreement Name
WELL X WELL	OTHER-		
2. Name of Operator			8. Farm or Lease Name
AMOCO PRODUCTION CC	MPANY		South Hobbs (GSA) Unit
P. O. Box 68, Hot	obs. NM 88240		9. Well No. 153
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER	05 - NC	orth 1485	Hobbs GSA
		•	
THE West LINE, SECTION	4 9 TOWNSHIP	19-S RANGE 38-E	_ NMPM. (())))))))))))))))))))))
	((((()	whether DF, RT, GR, etc.)	12. County
	3598	3.1' GL	Lea
Check A	ppropriate Box To India	cate Nature of Notice, Repor	or Other Data
NOTICE OF IN			QUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDO		ALTERING CASING
PULL OR ALTER CASING	Change Plans	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
Poet of Action Casing	CHANGE PEARS	OTHER Status U	
OTHER		_[]	·
	(6)		
work j SEE RULE 1103.	rations (Clearly state all pertin	ent details, and give pertinent dates,	ncluding estimated date of starting any proposed
service unit 11-23-83. Pulled tubing. Set a Drilled out cement and Andres Zones II and II and 4221'-24' w/4 JSPF acid. Pulled up and s Flushed with 27 bbl wa landing seating nipple and tested OK. Moved	Pulled rods and p cement retainer at d cement retainer. I intervals 4152'-5 . Ran packer and 2 set the packer at 40 deter. Pulled tubing e at 4230'. Install out service unit 11	4235' and capped with 1 Displaced well with fre 67', 59'-62', 67'-71', 7 P-7/8" tubing to 4220' a 100'. Pumped 3000 gal 1 and packer. Ran 2-7/8 ed production equipment -27-83. Pump tested fo	and 1 MCFD. Moved in installed blowout preventer. 50 sacks class C neat cement. sh water. Perforated San 8'-82', 94'-4200', 07'-11', nd spotted 4 bbl 15% NE HCl 5% NE HCl acid with additives. "tubing and seating nipple, Tested pump to 500 psir 4 days. Last 24 hours -30-83. Well is currently
0+5-NMOCD, H 1-R.E.Og 1-Shell		sh, Hou 1-CLF 1-Pet	ro Lewis 1-Texaco 1-Sun
PICHED Cathy Jos	man TITLE	Assist. Admin. Analys	t 12-13-83
ODICINAL CIONE	D BY JERRY SEXTON		
	SUPERVISOR TITLE	t	DEC 15 1983
· · · · · · · · · · · · · · · · · · ·			