

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	28337 30-025-99000
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-1961-1
7. Lease Name or Unit Agreement Name	New Mexico "J" State
8. Well No.	4
9. Pool name or Wildcat	Eunice Monument GBSA
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3711 GR

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

2. Name of Operator
Texaco Producing Inc.

3. Address of Operator
P. O. Box 730 Hobbs, NM 88240

4. Well Location
Unit Letter F : 1980 Feet From The North Line and 2310 Feet From The West Line
Section 24 Township 19S Range 36E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work) SEE RULE 1103.

- 1.) Notify OCD 24 hours prior to commencement of plugging operations.
- 2.) MIRUPU. TIH w/ 2 3/8" workstring. Tag plug at 3705'.
- 3.) Load hole w/ 9.5 ppg mud. Spot additional 3 sxs. (Class "H" w/ 2% CaCl2, 5.2 gal/sack, 15.6 ppg, 1.18 cu. ft/ sack) on top of existing plug at 3705'.
- 4.) Spot 220' cement plug across top of salt from 1220' to 1440'. (26 sxs. Class "H" 1.18 cu. ft/ sack w/ 2% CaCl2)
- 5.) Spot 220' cement plug across 8 5/8" csg shoe from 290' to 510'. (26 sxs. Class "H" 1.18 cu. ft/ sack w/ 2% CaCl2)
- 6.) Spot 10 sack plug from 88' to surface.
- 7.) Cut off wellhead. Install hole marker. Clean location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry D. Ridenour TITLE Engineer's Assistant DATE 11-21-90

TYPE OR PRINT NAME Larry D. Ridenour TELEPHONE NO. 393-7191

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: _____