

Sample	Depth	Grain Dens	Poro sity	Kv	Permeability Max.	90	SW	SO	Flo	Remarks
176		3856	2.82	4.4	0.01	0.06	0.05	82.2	0.0	TrB/O Dolo, Silty, S/P, Sty, Fr.
177		3857	2.83	3.4	0.02	0.10	0.07	69.0	8.6	TrB/O Dolo, S/P, Fr.
178		3858	2.83	2.6	0.01	0.06	0.05	85.6	0.0	TrB/O Dolo, S/P, Sty, Fr.
179		3859	2.84	2.7	0.02	0.23	0.19	69.2	18.1	50 Dolo, Silty, Sc. Lam. S/P, Sc. Vugs, Fr.
		3859.5	SCAL							
180	3859.5	3860	2.83	7.7	*0.04	0.57	Plug	34.0	6.8	100 Dolo, Sty, Vugy, Fr.
181		3861	2.85	5.5	0.13	0.76	0.73	41.9	12.0	100 Dolo, Sty, Sc. Vugs, Fr.
182		3862	2.84	4.6	0.03	0.18	0.06	70.2	0.0	10 Dolo, Sty, Sc. Vugs, Fr.
183		3863	2.85	5.5	*0.03	0.01	Plug	47.4	18.9	Sp.60 Dolo, S/P, Sty, Sc. Vugs, Fr.
184	3863	3864	2.80	5.7	*0.03	0.02	Plug	52.4	9.2	Sp.30 Dolo, Silty, Sli. Shaly, S/P, Fr.