

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31901 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E 1587
7. Lease Name or Unit Agreement Name Lea AQ State
8. Well No. 6
9. Pool name or Wildcat Pearl San Andres, West
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3765.5 RKB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Matador Operating Company

3. Address of Operator
415 W. Wall, Ste 1101, Midland, TX 79701

4. Well Location
Unit Letter L : 330 Feet From The west Line and 1650 Feet From The south Line

Section 29 Township 19S Range 35E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3765.5 RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded @ 8:30 PM (CST) 3-1-93. Drilled 12-1/4" hole to 445' KB. Ran 10 jts new 8-5/8", 24#, J-55, ST&C casing, set @ 445' KB. Cemented w/275 sx Class C, 2% CaCl₂, 1/4#/sk celloflakes. Displace with fresh water. PD @ 7:30 AM (CST) 3-2-93. Release to float and held OK. Circulate 10 bbls cement to surface. Test BOP pipe and blind rams to 750 psi. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Operations Manager DATE 3-8-93

TYPE OR PRINT NAME R. F. Burke TELEPHONE NO. 915-687-5955

(This space for State Use)

APPROVED BY [Signature] TITLE Operations Manager DATE 3-8-93

CONDITIONS OF APPROVAL, IF ANY: