Submit 3 Copies to Appropriate

State of New Mexico Energy, nunerals and Natural Resources Department

Form C-103

Revised 1-1-89 District Office OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-32032 DISTRICT I Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. E-5231 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: WELL X Anasazi "4" State WELL. OTHER 2. Name of Operator & Well No. Bass Enterprises Production Co. 3 3. Address of Operator 9. Pool name or Wildcat P 0 Box 2760 Midland, Tx 79702-2760 West Teas (Yates/Seven Rivers 4. Well Location __ Line and __1980 1650 Feet From The South _ Feet From The <u>Fast</u> Line Range 33E Township 20S NMPM Lea, N.M. County Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3531' GR 3547' KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT TEMPORARILY ASANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER Spud date & surface casing OTHER: 12. Describe Proposed or Completed Operations (Clearly state all partinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spud 7:00 AM 11-8-94. Drilled 12 1/4" hole to 1368' 11-9-94. Ran 2 jts 8 5/8" 32# K-55 ST&C casing. Ran 31 jts 8 5/8" 24# K-55 ST&C casing. Total of 33 jts. Set @ 1368'. Cemented w/710 sx Class "C" cement w/additives. Circ 258 sx to surface. WOC 16 hrs. Test wellhead to 1000 psi, OK. NU BOPE. Test rams to 1000 psi, OK. Test choke manifold to 1000 psi, OK. Test 8 5/8" casing to 600 psi, OK. Test pipe rams & Hydrill to 1000 psi, OK. Drill float collar & cement & shoe OK. Drilling 7 7/8" hole. I hereby certify that the information above is integrand complete to the best of my knowledge and belief. B.C. Houtchens The Senior Production Clerk DATE 11-11-94

SIGNATURE ... TELEPHONE NO. TYPE OR PRINT NAME Orig. Signed by (This space for State Use) Paul Kautz 1954 Geologist 14 J V APPROVED BY-