

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Amerada Hess Corporation

3. Address and Telephone No.

P.O. Box 2040, Houston, TX 77252-2040

(713)609-4846

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 330' FEL (NE/NE) SEC. 3 T20S-R36E

FORM APPROVED

Budget: Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-1150

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

REED "A-3"

FEDERAL #16

9. API Well No.

30-025-33300

10. Field and Pool, or exploratory Area

MONUMENT ABO

11. County or Parish, State

LEA, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other RUNNING 5-1/2" CSG.
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-20-96 RU WEATHERFORD CSG. CREW & RUN 176 JTS. OF 5-1/2", 15.50#, K55, 8 RL, SMLS, R-3, "A" CSG SET @ 7,661', SHOE @ 7,659', FC @ 7,568'. D.V. TOOL @ 4,662'. RAN 70 TURBOLIZERS & 27 CENTRALIZERS. CMT. W/DOWELL - PUMP 100 BBLS TREATED CHEMICAL WASH, 100 SX CLASS "C", 50:50 POZ + 8#/SX D44 + .4% D59 + 1/4#/SX. C.F. (14.1# 1.46) 200 SX CLASS H + 6#/SX D44 + .9% D59 + .3% D65 + 2% D79 + 1/4#/SX. C.F. (15.6# 1.26) DISPL. W/180 BBLS (70 BBLS. F. WATER, 110 BBLS MUD) @ 8 BBLS/MIN. FINAL CIRC. W/850 PSI. BUMP PLUG W/1350 PSI @ 1:00 A.M. 3/21/96. STOP RECIPROCATING CSG. AFTER 150 BBLS. DISP. W/RETURNS THROUGHOUT JOB. EST. TOC @ 6,100'. DROP BOMB & OPEN STAGE TOOL W/950 PSI. CIRC. 5-1/2" CSG. CIRC. 30 BBLS. CHEMICAL WASH TO PIT. CMT 2ND STAGE. PUMP 100 BBLS. TREATED WATER, 450 SX. CLASS "C", 50:50 POZ + 8#/SX. D44 + .4% D59 + 1/4#/SX. C.F. (14.1# - 1.46) 100 SX. CL. "H" + 6#/SX D44 + .9% D59 + .3% D65 + 2% D29 + 1/4#/SX. C.F. (15.6# 1.26) BUMP PLUG & CLOSE STAGE TOOL W/2500 PSI @ 6:30 A.M. GOOD RETURNS THRU-OUT JOB. CIRC. 45 BBLS TREATED WATER TO PIT. EST. TOP OF CMT. @ 2500'. NU BOP. TEST W/2200 PSI. O.K.

ACCEPTED FOR RECORD

APR 12 1996

14. I hereby certify that the foregoing is true and correct

Signed

Mike Jumper

Title

ADM. SUPERVISOR DRILLING SVS.

Date

03-22-96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side