Submit 3 Copies to Appropriate District Office

APPROVED BY\_

CONDITIONS OF APPROVAL, IF ANY:

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

**DISTRICT I** OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 WELL API NO. P.O. Box 2088 30-025-33514 Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease DISTRICT III STATE FEE XX 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" 7. Lease Name or Unit Agreement Name (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Royal Wulff WELL XX WELL OTHER 2. Name of Operator 8. Well No. David H. Arrington Oil & Gas, Inc. 3. Address of Operator 9. Pool name or Wildcat P.O. Box 2071, Midland, Texas 79702 4. Well Location Monument Abo Unit Letter P : 330 Feet From The South Line and 330 \_\_\_\_ Feet From The East Line Township 19-S Range 36-E **NMPM** 10. Elevation (Show whether DF, RKB, RT, GR, etc.) County 3664' GL, 3681' KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB X OTHER: OTHER:\_ 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed 8/13 & 8/14/96 Spud well. Drill 17 1/2" hole to 312'. Set 13 3/8", 48#, H-40 casing @ 312' and cemented to surface with 350 sx "C". Circulated 57 sx. WOC 12 hrs. and tested casing to 1000 psi. 8/18/96 Drilled 11" hole to 3050'. Set <u>8 5/8</u>", 24# and 32#, J-55 casing @ 3050' and cemented with 675 sx light "C" follwed by 150 sx "C". Circualted 89 sx to surface. WOC 12 hrs. and tested casing and BOP to 1000 psi OK. 8/29/96 Drilled 7 7/8" hole to 8020'. Set  $5\frac{1}{2}$ ", 15/5# and 17#, J-55, casing @ 8020'. Cemented with 575 sx Light "C" followed by 400 sx "C". Top of cement 2920' CBL. Tested casing to 2700 psi OK. Released Rig. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SKONATURE 200 h \_ DATE <u>9-20-96</u> TYPEOR PRINT NAME David H. Arrington TELEPHONE NO. 915-682-6685 (This space for State Use)

TITLE -