

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Co.
F. 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

| | |
|--|---|
| 1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other | 5. Lease Designation and Serial No. LC 031622A |
| 2. Name of Operator Conoco, Inc. | 6. If Indian, Allottee or Tribe Name |
| 3. Address and Telephone No. 10 Desta Dr., Suite 100W, Midland, TX 79705 915-686-5400 | 7. If Unit or CA, Agreement Designation |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2310' FSL & 1650' FEL Sec. 11, T-20S, R-36E | 8. Well Name and No. Klein Federal No. 1 |
| | 9. API Well No. 30-025-33761 |
| | 10. Field and Pool, or Exploratory Area |
| | 11. County or Parish, State Lea, NM |

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| TYPE OF SUBMISSION | TYPE OF ACTION |
|--|--|
| <input checked="" type="checkbox"/> Notice of Intent | <input checked="" type="checkbox"/> Abandonment |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion |
| <input type="checkbox"/> Final Abandonment Notice | <input type="checkbox"/> Plugging Back |
| | <input type="checkbox"/> Casing Repair |
| | <input type="checkbox"/> Altering Casing |
| | <input type="checkbox"/> Other |
| | <input type="checkbox"/> Change of Plans |
| | <input type="checkbox"/> New Construction |
| | <input type="checkbox"/> Non-Routine Fracturing |
| | <input type="checkbox"/> Water Shut-Off |
| | <input type="checkbox"/> Conversion to Injection |
| | <input type="checkbox"/> Dispose Water |

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Set a CIBP at 8600'. Spot 35' cement on top.
- Cut and pull 5 1/2" casing at +- 6000'.
- Spot 30 sxs cement casing stub plug 5950-6050'. Tag plug.
- Circulate hole with mud.
- Spot 30 sxs cement 3918-4018'. Tag plug.
- Spot 30 sxs cement 1100-1200'.
- Spot 30 sxs cement 371-471'.
- Spot 10 sxs surface cement plug.
- Install dryhole marker. Clean location.

14. I hereby certify that the foregoing is true and correct

Signed Kay Maddox Title Regulatory Agent Date Oct. 20, 1997

(This space for Federal or State office use)

Approved by BRIG. SGD. DAVID Z. GLASS Title PETROLEUM ENGINEER Date NOV 03 1997

Conditions of approval, if any:

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CURRENT WELLBORE

7/15/97

Elev. 3569' GR +17' KB

421' - 11 3/4" Casing
Cemented w/360 sxs. Circulated to Surf.

3968' - 8 5/8" Casing.
Cemented w/880 sxs. Circulated to Surf.

T.O.C. @ 6000' (Estimated)

Perfs 8681'-8729'

C.I.B.P. @ 8800' w/35' Cement on Top.

Perfs 8816'-8880'

C.I.B.P. @ 9000' w/35' Cement on Top.

Perfs 9009'-9049'

9155' - 5 1/2", 17# Casing.
Cemented w/560 sxs

T.D. @ 9200'

| |
|-----------------------|
| CONOCO, INC. |
| Klein Federal No. 1 |
| 2310' FSL & 1650' FEL |
| Sec. 11, T-20S, R-36E |
| Lea County, N.M. |

PROPOSED PLUG AND ABANDONMENT

7/15/97

Elev. 3569' GR +17' KB

SPOT 10 SXS CEMENT SURFACE PLUG

SPOT 30 SXS CEMENT 371'-471'

421' - 11 3/4" Casing

Cemented w/360 sxs. Circulated to Surf.

SPOT 30 SXS CEMENT 1100'-1200'

SPOT 30 SXS CEMENT 3918'-4018'

3968" - 8 5/8" Casing.

Cemented w/880 sxs. Circulated to Surf.

CUT & PULL 5 1/2" CASING @ +-6000'

SPOT 30 SXS CEMENT 5950'-6050' STUB PLUG

T.O.C. @ 6000' (Estimated)

C.I.B.P. @ 8600' w/35' Cement on Top.

Perfs 8681'-8729'

C.I.B.P. @ 8800' w/35' Cement on Top.

Perfs 8816'-8880'

C.I.B.P. @ 9000' w/35' Cement on Top.

Perfs 9009'-9049'

9155' - 5 1/2", 17# Casing.

Cemented w/560 sxs

T.D. @ 9200'

CONOCO, INC.

Klein Federal No. 1

2310' FSL & 1650' FEL

Sec. 11, T-20S, R-36E

Lea County, N.M.