INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	1677.0	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2852.0	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers	3084.0	T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4376.0	T. Simpson		T. Gallup		T. Ignacio Otzte	
T. Glorieta	5615.0	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Blinebry	6067.0	T. Gr. Wash		T. Morrison		T.	
T. Tubb	6594.0	T. Delaware Sand		T. Todilto		T.	
T. Drinkard	6703.0	T. Bone Springs		T. Entrada		T.	
T. Abo	7224.0	T.		T. Wingate		T.	
T. Wolfcamp	7925.0	T.		T. Chinle		T.	
T. Penn		T.		T. Permain		T.	
T. Cisco (Bough C)		T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from 6968 to 7065 No. 3, from ..... to .....

No. 2, from 7341 to 7542 No. 4, from ..... to .....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from ..... to ..... feet .....

No. 2, from ..... to ..... feet .....

No. 3, from ..... to ..... feet .....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0.0	1703.0	1703.0	Sand-caliche				
1704.0	2852.0	1148.0	Salt & anhydrite				
2853.0	4376.0	1523.0	sand & dolomite				
4376.0	8000.0	3634.0	Dolomite & Limestone				