

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

E-396-6

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water injection well	7. Unit Agreement Name Cone Jalmate Yates Pool
2. Name of Operator J.R. Cone	8. Farm or Lease Name Tract 9
3. Address of Operator P.O. Box 10217 Lubbock, Texas 79408	9. Well No. 2
4. Location of Well UNIT LETTER P 990 FEET FROM THE South LINE AND 330 FEET FROM East 25 TOWNSHIP 22S RANGE 35E N.M.P.M.	10. Field and Pool, or Wildcat Jalmate (011)
15. Elevation (Show whether DF, RT, GR, etc.) 3545 GR, 3554 KB (datum)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Basic Well Data:

TD 5 1/2" 14# csng cemented @ 3851' w/250 sax 7 7/8" hole
8 5/8" 24# csng cemented @ 300' w/250 sax 12 1/4" hole
Yates Perforated 3711'-3725' and 3747' 3761'
Baker tension packer on 2 3/8" tubing set at 2956'

11-7-85

Released packer and pulled tubing
Set cast iron bridge plug @ 2974 and perforate 2970 w/ 4 holes.
Pressure to 2000#. Unable to pump into circulated hole with mud.
Mix 25 sacks cement 2974 to 2761. 25 sacks cement 1668 to 1498.
Perforate 4 holes @ 300'. 50 sacks cement displaced to 250', S.D.
5hrs test 500#, 5sack surface plug install marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James K. [Signature]

TITLE Agent

DATE 9-12-86

APPROVED BY R. [Signature]

TITLE OIL & GAS INSPECTOR

DATE 10-1-86

CONDITIONS OF APPROVAL, IF ANY: