

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

DEC 22
SUBMIT IN TRIP
(Other instructions
verse side)

OFFICE O. C. C.

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-030132 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SECTION, TOWNSHIP, RANGE, AND SURVEY OR AREA

12. COUNTY OR PARISH 18. STATE

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Cities Service Oil Company

3. ADDRESS OF OPERATOR
% Hobbs Pipe & Supply Co., Box 2010, Hobbs, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

0 660' from south line and 1980' from the east line.

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)
3590

Lea N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Propose to spot a 25 sack cement plug at 3825'.
- ~~Propose to spot a 25 sack cement plug at 2000', stub of 5 1/2".~~
- Propose to spot a 25 sack cement plug at 1562', shoe of 8 5/8".
- Propose to spot a 10 sack cement plug at surface with marker.
- Hole will be loaded with mud laden fluid.

AMENDMENT: Instead of No. 2 above, place 25 sack cement plug at 3150-3250 feet.

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE Agent DATE 12-16-69

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED
DEC 19 1969
ARTHUR R. BROWN
DISTRICT ENGINEER