

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
 State Fee
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO ABANDON OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE APPLICATION FOR PERMIT TO PLUG BACK TO A DIFFERENT RESERVOIR FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- **Water Supply Well**

2. Name of Operator
Gulf Oil Corporation

3. Address of Operator
Box 670, Hobbs, New Mexico 88240

4. Location of Well
 UNIT LETTER **C** **660** FEET FROM THE **North** LINE AND **1650** FEET FROM
 THE **West** LINE, SECTION **14** TOWNSHIP **22-S** RANGE **35-E** N.M.P.M.

15. Elevation (Show whether DF, RT, CR, etc.)
3600' GL

7. Unit Agreement Name
Jalmat Field Yates Sand Unit

8. Form of Lease Name

9. Well No.
125

10. Field and Pool, or Wildcat
Jalmat

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER _____	

Plugged and abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spotted 25 sacks, 100' cement plug on top of CIBP at 4075'. Loaded hole with abandonment mud. Spotted 60 sack, 125' cement plug from 2075' to 1950'. Pumped 190 sacks of Class C cement containing 3% Ca Cl2 and 100 sacks of Class C neat cement thru hole in 13-3/8" casing at 110' and circulated out 13-3/8" - 20" annulus to surface. Tag cement inside 13-3/8" casing at 15'. Spotted cement plug from 15' to surface. Installed dry hole marker. Plugged and abandoned November 22, 1976.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. R. Koyckawa TITLE Project Petroleum Engineer DATE November 23, 1976

APPROVED BY John W. Rumpac TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

1967 JUN 27 10 57 AM
U.S. DEPARTMENT OF COMMERCE
WASHINGTON, D.C.