

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32255
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-0134
7. Lease Name or Unit Agreement Name Kiwi AKX State
8. Well No. 9
9. Pool name or Wildcat East Livingston Ridge Delaware
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3781' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location
Unit Letter A : 330 Feet From The North Line and 330 Feet From The East Line
Section 16 Township 22S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3781' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Spudded 26" hole 1:15 PM 10-11-93 with Frank's Rathole Service. Set 57' of 20" conductor pipe and cemented to surface. Notified NMOCD, Hobbs, NM of spud. Resumed drilling 17-1/2" hole 10:30 PM 10-12-93. Ran 21 joints 13-3/8" 54.5# J-55 casing set 870'. Guide shoe set 870', insert float set 828'. Cemented w/500 sx PSL "C" + 2% CaCl2 (yield 1.76, wt 12.9). Tailed in w/250 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:46 PM 10-14-93. Bumped plug to 300 psi, float held OK. Circulated 240 sacks. WOC. Drilled out 6:30 PM 10-14-93. WOC 18 hours and 35 minutes. NU and tested. Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-18-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR
APPROVED BY _____ TITLE _____ DATE **OCT 20 1993**
CONDITIONS OF APPROVAL, IF ANY: