
NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified begin. A convey will be sended on which will be given the convey will be sended on which will be given the convey of which will be given the convey of the sender on which will be given the convey of the sender on which will be given the convey of the sender on which will be given the convey of the sender of

advisable, or the rejection by the Commission or agent, of and work should not begin until approval is obtained. Such a Commission.	the plan submitted. The plan as see additional instructions in	s approved should be the Rules and Regul	followed, ations of
	otice by checking below:		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL		
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL		I
NOTICE OF INTENTION TO DEEPEN WELL			
	Hobbs, New Mexico	May 10, 195	ю
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen: Following is a notice of intention to do certain work as described to the standard of the company of the com	exander *B* Wel	l No. 1 in 1	W/L Field.
FULL DETAILS OF PROFOLLOW INSTRUCTIONS IN THE RULES	POSED PLAN OF WORK		
Deeper production has been condent Alexander "B" No. 2.	med by virtue of deepe		
The following casing strings are 13" casing '70# @ 146' cemented wi 9-5/8" casing 36# @ 1341' cemente 7" casing 22# @ 3516' cemented wi An attempt will be made to recove and 7" casing strings, and cement plugs the salt section and all fluid bearing z	th 100 sacks in 17" hod with 500 sacks in 12 th 300 sacks in 8-3/4" r the uncemented portiplaced as follows in o	ole. 2" hole. hole.	
Approved MAY 1 2 135° , 19, 19, 19, 19	By Jan Hen Position Field Supe	or Operator	
OIL CONSERVATION COMMISSION, By MC MARKET COMMISSION,	Name Ralph L. He	ndrickson	
Fitle Inaposition	Hobbs, New		

20 sacks cement plug in 7" csg. stub 3516-3416' 1450-1550' At Surface

A heavily mud laden fluid will be mixed and placed between all cement plugs. The location will be cleared and a 4" marker will be erected to extend 4 feet above the ground level, in compliance with New Mexico Oil Conservation Commission regulations.