

Approval expires 12-31-12

DUPLICATE
Form 9-22-9
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office 022076 (b)
Lease No. N.M.F.U.
Unit

ILLEGIBLE

RECEIVED
NOV - 6 1951
OFFICE OF CONSERVATION COMMISSION
SHUT-OFF HOBBES OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. M. Lockhart Well No. 4

Hobbs, New Mexico - November 5, 1951

Well No. 4 is located 330 ft. from N line and 1650 ft. from W line of sec. 11
SW/4 Sec. 11 (1/4 Sec. and Sec. No.)
North Bronson (Field)
21S (Twp.) 37E (Range) N.M.P.M. (Meridian)
Lea (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is our intention to drill a well with rotary tools at the above location to a total depth of approximately 7750', or to a depth sufficient to attempt completion in the Ellenburger horizon. All casing will be cemented in accordance with approved methods of the U. S. Geological Survey and any other special requirements will be complied with.

It is planned to use the following casing pattern: 10 3/4" casing to be set at approximately 250' and cemented with 250 sacks; cement to be circulated to surface; 7 5/8" casing to be set at approximately 3150' and cemented with 1,250 sacks or sufficient cement to protect the salt section; 5 1/2" casing to be set at approximately 7750' and cemented with 546 sacks or the required amount as determined by survey, casing to be perforated opposite the pay zone.

Approval to produce this well upon completion is also requested.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company
Address Box 427
Hobbs, New Mexico
W. A. Gaudin

By D. F. Jacobs
Title Asst. Dist. Supt.

23-100000

22
1992

20

42

100-443886-100

... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..
... ..

10-10-68

117