

A Subsidiary of O.P. Miller Company

Copyrighted Reproduction Prohibited

COUNTY	IEA	FIELD	Drinkard	STATE	NM
OPR	GULF OIL CORP.			API	MN 24024
NO	14	LEASE	Leonard, Harry (NCT-C)	SERIAL	10-1-19 NM
Sec 36, T-21-S, R-36-E				MAP	
1830' FNL, 910' FEL of Sec				CO-ORD	
2 mi W/Eunice				ELEV	
Re	8-18-75	Re	9-15-75	WELL CLASS:	DD
SPD		COMP		INIT	DD
CSG				FIN	DD
8 5/8" at 1236' w/400 sx 5 1/2" at 5991' w/625 sx 4" lnr 5781-6754' w/68 sx				FORMATION	DATUM
TD 6755' (DRKD)				PBD	6740'

IP (Drinkard) Perfs 6502-6677' F 152 BOPD + 88 BLW. Pot based on 24 hr test thru 16/64" chk, TP 340#

CONTR	Eunice Well Service	OPR'S ELEV	3485' GL	PD	6800' RT
-------	---------------------	------------	----------	----	----------

F.R. 8-11-75 OWDD
 (Drinkard)
 (Orig. comp 2-27-72 thru (Blinebry) Perfs 5494-5700', OTD 5991', OPB 5962')

8-26-75 Drlg 6559'

9-2-75 TD 6755'; PBD 6740'; WOC
 Deepened 5991' to 6755'
 Ran 4" lnr

9-8-75 TD 6755'; PBD 6740'; SI
 Perf (Drinkard) 6502-05', 6551-54', 6578-81',
 6628-31', 6652-55', 6674-77' w/4 SPF
 Acid (6502-6677') 2500 gals
 Swbd 40 BO + 90 BL & AR in 12 hrs (6502-6677')

10-1-19 NM

LEA
GULF OIL CORP.

Drinkard
14 Leonard, Harry (NCT-C)
Sec 36, T21S, R36E

NM

Page 2

9-15-75 TD 6755'; PBD 6740'; Swbg 1d
Frac (6502-6677') 30,000 gals wtr + 30,000# sd
9-22-75 TD 6755'; PBD 6740'; WO OCC Pot
Flwd 152 BO + 88 BLW in 24 hrs thru 16/64" chk,
TP 340# (6502-6677')
9-29-75 TD 6755'; PBD 6740'; Complete
Blinebry Perfs 5494-5700' Packed off
10-4-75 COMPLETION ISSUED

10-1-19 NM
30 025 70008 75

COUNTY LEA FIELD Blinebry STATE NM 30-025-24024

OPR GULF OIL CORP.

MAP

14 Leonard, Harry (NCT-C)

Sec 36, T-21-S, R-36-E

CO-ORD

1830' FNL, 910' FEL of Sec

Spd 2-8-72

CLASS

EL 34912

Cmp 2-27-72

FORMATION

DATUM

FORMATION

DATUM

CSG & SX - TUBING

8 5/8" at 1236' w/400 sx

5 1/2" at 5991' w/625 sx

LOGS EL GR RA IND HC A

TD 5991'; PBD 5962'

IP (Blinebry) Perfs 5494-5700' F 127 BOPD + 370 BLW. Pot based on 21 hr test thru 40/64" chk, CP 850#, TP 400#

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Moran

PROP DEPTH

6000'

TYPE

RT

DATE

F.R. 1-25-72; Opr's Elev. 3485' GL

PD 6000' RT (Blinebry)

Contractor - Moran

2-14-72 Drlg. 3272' lm

2-18-72 Drlg. 4780' lm

2-28-72 TD 5991'; PBD 5962'; Swbg Load
Perf 5494-98', 5542-46', 5600-04', 5633-37',
5660-64', 5696-5700' w/2 SPF
Acid (5494-5700') 1250 gals (15% NEA)
Frac (5494-5700') 29,000 gals jelled wtr +
30,000# sd

3-6-72 TD 5991'; PBD 5962'; COMPLETE

LOG TOPS: Anhydrite 1137', Yates 2620', Seven
Rivers 2878', Queen 3358', Grayburg 3636',
Glorieta 5150', Blinebry 5490'

3-11-72 COMPLETION REPORTED