

-----  
 Meter Run: 4.026 Orifice Size: 1.750" File #: 128404 Page: 1 of 1  
 DATE WLHD Static Diff Meter Gas Oil G.O.R. Water G.L.R.  
 or WHP CSG Temp Run  
 TIME PSIG PSIG DEG F PSIG INCH DEG F MSCF/D BBL/D SCF/BBL BBL/D SCF/BBL  
 -----

Feb 02, 1991

07:00											
											Arrive on location (well shutin)
08:36	3278										Run in S/L gauges
10:10											Open to purge lines
11:10											Open on 8/64" choke, 1st rate
11:15	2913			360	8	83					1062
11:30	2770			645	3	94					869
11:45	2754			900	2	116					826
12:00	2748			930	2	123					833
12:15	2737			915	2	123					826
12:30	2731			870	2	119					808
12:45	2731			862	2	104					819
12:45											Change to 10/64" choke, 2nd rate
13:00	2460			900	6	99					1462
13:15	2427			885	5	98					1324
13:30	2420			855	5	94					1306
13:45	2436			840	4	90					1163
13:45											Choke plugging
14:00	2424			840	4.25	88					1202
14:15	2392			855	4.50	84					1256
14:30	2368			870	4.50	84					1268
14:45	2350			870	4.75	87					1297
15:00	2349			875	4.75	88					1299
15:00											Change to 12/64" choke, 3rd rate
15:15	2175			885	8	90					1693
15:30	2107			892	7.75	91					1671
15:45	2082			885	8	90					1692
16:00	2032			900	8.25	90					1735
16:15	1950			900	8.50	96					1747
16:30	1920			892	10	105					1863
16:45	1915			900	11	111					1949
17:00	1915			900	11	112					1947
17:00											Change to 14/64" choke, 4th rate
17:15	1710			945	18	117					2541
17:30	1645			945	18.5	117					2576
17:45	1627			945	14	112					2255
18:00	1630			945	11	108					2008
18:16	1630			930	11	108					2000
18:16											End Test

COMMENTS: No liquids produced.