

[illegible]

M. J. A. Grimes
Mr. L. H. Shearer
NEW!
Mr. D. V. Kitley
Mr. T. A. Steele
Mr. T. O. Webb

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

State McDonald A/C 1 B

.....
(Company or Operator)

(Leave)

Well No. 9, in NW ¼ of SW ¼, of Sec. 36, T. 22S, R. 36E, NMPM.

South Evnice

Pool Lea

...County.

Well is 1650 feet from south line and 330 feet from west line

of Section 36 If State Land the Oil and Gas Lease No. is 106

Drilling Commenced 1/27/58, 19..... Drilling was Completed 2/5/58 19.....

Name of Drilling Contractor..... Carper Drilling Company

Address..... **Hobbs, New Mexico**

Elevation above sea level at Top of Tubing Head.....3159'..... The information given is to be kept confidential until
 -----, 19.....

OIL SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from.....to.....feet.....

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9-5/8"	32.3#	New	382'	Guide	-		Surface
5-1/2"	15.5#	"	3767'	Diff. fillip		3653'-3728'	Oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4"	9-5/8"	397'	250-3%	2 plug	-	-
7-7/8"	5-1/2"	3779'	1350	2 plug	-	-

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated Queen section thru 5 1/2" csg perfs 3653'-3728' with 500 gals mud acid & 10,000 gals 1#/gal sand/oil.

Result of Production Stimulation. Flowed 14.99 bbls oil, no water, in 8 hours on 15/64" choke at rate of 134.97 BOPD with FTP 170#, CP 200#, GOR 450:1

..Depth Cleaned Out.....3778' PBTD

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3780' TD feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 2/15/58, 19
OIL WELL: The production during the first 8 hours was 44.99 barrels of liquid of which 99.8 % was oil; % was emulsion; % water; and 0.2 % was sediment. A.P.I. Gravity 38.8° API @ 60° F.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1403' W/G-P meas.	T. Devonian	T. Ojo Alamo		
T. Salt	1578' "	T. Silurian	T. Kirtland-Fruitland		
B. Salt	2129' "	T. Montoya	T. Farmington		
T. Yates	3035' "	T. Simpson	T. Pictured Cliffs		
T. 7 Rivers	3305' "	T. McKee	T. Menefee		
T. Queen	3653' "	T. Ellenburger	T. Point Lookout		
T. Grayburg		T. Gr. Wash	T. Mancos		
T. San Andres		T. Granite	T. Dakota		
T. Glorieta		T.	T. Morrison		
T. Drinkard		T.	T. Penn.		
T. Tubbs		T.	T.		
T. Abo		T.	T.		
T. Penn		T.	T.		
T. Miss		T.	T.		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	310	310	Surface, Caliche				
310	1409	1099	Red Bed				
1409	1565	156	Anhydrite				
1565	2910	1345	Anhydrite, Salt				
2910	3376	466	Anhydrite				
3376	3500	124	Anhydrite, Dolomite				
3500	3780	280	Anhy, Dolo, Sand, Shale				
			3780' = T.D.				
			3778' = P.B.T.D.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

February 19, 1958 (Date)
Company or Operator THE OHIO OIL COMPANY Address Box 2107, Hobbs
Name ORIGINAL SIGNED BY B. G. HOWARD Position or Title Asst. Supt.