

ELEV. 3354 DF 0'-10' AGL

SALT TOP: 1178'

SALT BASE: 2340'

SEC 15-T225-R37E

330' FSL & 400' FEL

COMPLETION & WORKOVER HISTORY:

11-29-36: DRLD TO 3640'

SHOT W/210 QTS NITRO 3500'-3556'

TREATED W/3000 GALS ACID.

UNCEMENTED LINER SET @ 3370' TO 3556'

7-6-38: DEEPEMED TO 3685' W/CABLE TOOLS

TRTD W/2000 GALS ACID 3640'-3685'

4-6-74: CONVERTED TO INJECTION.

16", 70# SHLW, @ 228'
W/110 SX.

2 3/8" CL TBG, W/2"x2"
TENSION PKR & SET
@ 3347' W/12 PT TENSION.

8 5/8", 32# SHLW, @ 1132' W/300 SX.

3370'-3556'
UNCEMENTED LINER,
5 1/2", 17# SMLS, BOTTOM
2 JTS PERFORATED

3370'

7", 24# SMLS @ 3411' W/300 SX

3556'

TD: 3685'

CHECKED BY

DATE 10-28-78

PAGE 1 OF 1

COMP. RENTAL ...
CALCULATION SHEET

TITLE ELLIOT A-15 #1

WELL BORE DIAGRAM

LOG NO.

FIELD

STATE

NMFO

N.M.