

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

CHANGE OPERATOR NAME FROM
HUMBLE OIL & REFINING COMPANY
TO EXXON CORPORATION
EFFECTIVE JANUARY 1, 1973

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator HUMBLE OIL & REFINING COMPANY	8. Farm or Lease Name W. B. FERREL
3. Address of Operator P.O. BOX 1600, MIDLAND, TEXAS 79701	9. Well No. 3
4. Location of Well UNIT LETTER J, 2180 FEET FROM THE EAST LINE AND 1880 FEET FROM THE SOUTH LINE, SECTION 22, TOWNSHIP 22-S, RANGE 37-E, NMPM.	10. Field and Pool, or Wildcat DRINKARD
15. Elevation (Show whether DF, RT, GR, etc.) 3358 DF	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. SET 50 SX CLASS H CEMENT PLUG AT 6440-6000, TESTED PLUG W/1000 PSI, HELD OK.
2. CUT 2" TBC AT 3787 AND PULLED
3. SET 25 SX CLASS H CEMENT PLUG FROM 3785-3585.
4. CUT 5 1/2" CSG AT 3502 AND PULLED.
5. SET 200 SX CLASS H CEMENT PLUG FROM 3502-3100.
6. SET 100 SX CLASS H CEMENT PLUG FROM 3100-2883, TESTED PLUG W/200 PSI, HELD OK.
7. SET 75 SX CLASS H CEMENT PLUG FROM 2883-2500.
8. LOADED HOLE WITH MUD LADEN FLUID AND SET 10 SX CLASS H CEMENT SURFACE PLUG.
9. INSTALLED DRY HOLE MARKER AS REQUIRED BY NMOCC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>UNIT HEAD</u>	DATE <u>11-27-72</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		