

Mr. J. A. Grimes
Mr. L. H. Shearer
Mr. D. V. Kitley
Mr. T. A. Steele
Mr. T. O. Webb

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE & sandfrac	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) Dual Complete	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 21, 1958
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

THE OHIO OIL COMPANY J. L. Muncy Well No. 2 in K
(Company or Operator) Lease (Unit)
NE 1/4 SW 1/4 of Sec. 24, T. 22S, R. 37 E, NMPM, Drinkard Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

6895' TD, 6453' PB. 13-3/8" @ 299' with 250 sx, 8-5/8" @ 2801' with 1500 sx, 5 1/2" @ 6505' with 650 sx.

Plan to abandon Drinkard oil zone & dual complete to Blinebry (Gas)/Tubb (Gas) as follows: Move in pulling unit, pull 2" tbg & pkr, set retainer @ approx. 6300' & squeeze Drinkard perfs 6390'-6410' with approx. 100 sx cement, plugging off Drinkard oil zone. Perf 5 1/2" csg in Tubb gas section approx. 5855'-6120' & treat with 750 gals mud acid & 20,000 gals sand/oil. Perf 5 1/2" csg in Blinebry gas section approx. 5412'-5525' & treat with 500 gals mud acid and 20,000 gals sand/oil. Set Baker Model "D" prod. pkr @ approx. 5800', run 2" tbg with latching seal assembly, tail pipe & Garrett valve & latch up pkr. Swab in both zones & test.

Above work approved by Order #DC-630, July 7, 1958

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By [Signature]
Title.....

THE OHIO OIL COMPANY

Company or Operator

By.....
Original Signed By
B. C. HOWARD

Position.....
Superintendent
Send Communications regarding well to:

Name.....
The Ohio Oil Company

Address.....
Box 2107, Hobbs, New Mexico