

LIST TYPE OF STRING BY CODE LETTERS, I.e. CONDUCTOR (C); SURFACE (S); INTERMEDIATE (I); PRODUCTION (P); LINER (L); PERFORATIONS (PP)

TYPE OF STRINGS & INTERVAL (FT)

FROM-TO	OD	DRIFT ID	WT PER FT	GRADE	THREAD	AMT	WT. IN AIR, 1000 LBS	WT. IN MUD 1000 LBS	REMARKS
(S) 0' - 1600'	8 5/8"	7.972"	24.00	K-55	STC	1600'	38.4		
(P) 0' - 3880'	5 1/2"	4.825"	15.50	K-55	STC	3880'	60.2		Sand blast bottom 30

TYPE OF STRING

TYPE OF STRING	CENTRALIZERS INTERVAL NO. FROM-TO	SCRATCHER NO. INTERVAL NO. FROM-TO	OTHER ACCESSORY EQUIPMENT (SUCH AS DEGASSERS, MUD. CENTRIFUGE FLOAT COLLARS, ETC. - SPECIFY)	REMARKS
(S) Surface	100' Spacing (16) 0'-1600'	15' Spacing None	Guide shoe and float collar	
(P) Production	(2) 1450'-1550' (above 8 5/8" shoe) (9) 3520-3880' (over pay zone)	(22) 3550'-3880' 15' spacing (over pay zone)	Float shoe and float collar	