

WESTATES PETROLEUM CORPORATION

RECEIVED

NOV 1957

OFFICE OF THE SECRETARY OF THE OIL FIELD

WESTATES PETROLEUM CORP. OF TEXAS

HISTORY OF OIL OR GAS WELL

WOOLLEY NO. 1

Spudded 12:15 a. m., 4-15-57. Drilled 12 $\frac{1}{4}$ " rotary hole to 625' and 11" rotary hole to 740'. Set and cemented 585.17' of new 8-5/8" J-55 24# 8rd. thd. ST&C casing at 597.17' using 300 sks. 50/50 poxmix cmt. and 75 sks. neat cmt., Halliburton method, Texas Pattern Shoe, float collar and one centralizer. Cmt. circulated to surface, plug down at 8:30 pm m., 4-15-57.

Drilled 7-7/8" rotary hole to 5010'. Cored from 5010' to 5026' and from 5026' to 5063', T.D. There were no show of oil or gas. B. Salt-4730', T. Dele. Line 4967' and T. Dele. Sand 5012' by gamma ray-neutron log.

Plugged w/cmt. fr. 5000' to 4950', 1290' to 1150' and 50' to surface, 4-29-57.

COPY

WISCONSIN HISTORICAL SOCIETY

RECORDS OF THE SOCIETY

RECORDS OF THE SOCIETY

RECORDS OF THE SOCIETY

RECORDS OF THE SOCIETY

RECORDS OF THE SOCIETY

RECORDS OF THE SOCIETY