



COPY 1-1-1-1

HOBBBS

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.

Land Office \_\_\_\_\_

Lease No. L.C. 071985

Unit \_\_\_\_\_

RECEIVED

JUN 15 1959

U. S. GEOLOGICAL SURVEY  
HOBBBS, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 12, 1959

Well No. 1 is located 30 ft. from N line and 30 ft. from E line of sec. 31

N. 10. 10. 10. (Twp.) 10. 10. 10. (Range) 10. 10. 10. (Meridian)  
(1/4 Sec. and Sec. No.)  
Undesignated (Field) 10. 10. 10. (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3,000 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Proposal is to set 8-1/2" O.D. 20 lb. casing with float valve at approximately 275 feet and circulate cement to the surface. To drill approximately 250 feet into the Delaware sand to a total depth of 1,000 feet. To set 10-1/2" O.D. 40 lb. casing at total depth and cement with 125 sacks of cement. Completion will be through perforations opposite Delaware formation after 300 gallons of acid and 100 lb. of treatment. Approximate spudding date June 17, 1959 with rotary tool. The well will be rotary cored and logs run.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company George L. Buckner, Inc.

Address Box 387

Mountain, Texas

By (Robert A. Orr)

Title Chief Engineer

June 12, 1950

George L. Duckins Company

530

Lea

Federal

26-5

East

Undesignated

Section B

BUCKLES

JUNE 12, 1950  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

George L. Duckins Company

Robert (Mr)

Box 507, Monahans, Texas

27 26  
34 35

②

①

330' to 370'

NEW MEXICO  
TEXAS

JUNE 12, 1950

2114

INSTRUCTIONS FOR COMPLETION:

1. Operator shall furnish and certify to the information called for in Section A.
2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plat the location of the well and certify this information in the space provided.
4. All distances shown on the plat must be from the outer boundaries of Section.
5. If additional space is needed for listing owners and their respective interests as required in question 3, Section A, please use space below

\* "Owner" means the person who has the right to drill into and to produce from any pool and to appropriate the production either for himself or for himself and another. (65-3-29 (e) NMSA 1953 Comp.)