

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1935' FNL } 330' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐☐  
☐  
☐  
☐  
☒  
☐  
☐  
☐  
☐

5. LEASE

Y.M. 02791 a

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

North El Mar

8. FARM OR LEASE NAME

North El Mar

9. WELL NO.

56

10. FIELD OR WILDCAT NAME

El Mar Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 31, T24S, R233E

12. COUNTY OR PARISH

13. STATE

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3075' Gm

RECEIVED

(NOTE: Report results of multiple completions or zone change on Form 9-330.)

JAN 5 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Casing in subject well repaired as follows:

12-4 Mieu Broke down wellhead

12-8 ran prod eqpt.

12-5 cut 4 1/2" csg below slips (114')

12-9 red rig

pulled 4 1/2" csg out of hole

12-28 pumped 980 93BW, 30 MCWG

12-6 screwed new casing in

12-7 Repl. 7 5/8" csg @ 6' by cutting

old csg off and splicing new on.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. D. B. [Signature] TITLE Admin. Supr.

DATE 1-3-79

(This space for Federal or State use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

U5G3 5

Partners 9

7/11e

ACCEPTED FOR RECORD

JAN 5 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

COPY TO O. C. C.

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1935' FNL, 330' FWL

AT TOP PROD. INTERVAL: ☒

AT TOTAL DEPTH: ☒

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☒

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 02791-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

North El Mar Unit

8. FARM OR LEASE NAME

North El Mar

9. WELL NO.

56

10. FIELD OR WILDCAT NAME

El Mar Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 31, T-26S, R-33E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3075' GR

(NOTE: Report use of multiple completion or zone changes on Form 9-330.)

RECEIVED  
DEC 8 1978  
U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

In order to effect casing repair on subject well, it is proposed to do the following:

- Unscrew 4 1/2" prod. csg @ 114' and replace split joint.

- Also we plan to repair the surface csg as follows:

- Cut surf. csg at weak spot approx. 8' below surface, and weld the well head on at this point. The surf. csg may be surrounded by cement during repair.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. Duttonfield

TITLE Admin. Supr.

DATE 12-6-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

2565 5  
Pantera 9

File

\*See Instructions on Reverse Side

APPROVED  
DEC 8 1978  
ACTING DISTRICT ENGINEER