

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	XXX		

Odessa, Texas

January 16, 1942.

Place

Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Phillips Petroleum Co. C. D. Woolworth Well No. 4 in the

SW/4 SW/4 of Sec. 23, T. 24-S, R. 36-E, N. M. P. M.,

Cooper Field, Lea County

The dates of this work were as follows: January 1, 1942 to January 9, 1942, Inc.

Notice of intention to do the work was ~~XXXX~~ submitted on Form C-102 on December 13, 1942 and approval of the proposed plan was ~~XXXX~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

T.D.3244. Ran 2" tubing to bottom & loaded hole with heavy mud. Ran 35 sacks cement from 3244-3195'. Loaded hole with heavy mud to 2570. Dumped 5 sacks cement from 2570-2547'. Shot 7" casing loose at 2450'. Recovered 2479'(overall) 7" casing. Filled hole with heavy mud from 2450-1380'. Ran tubing & spotted 35 sacks cement at 1380'. Filled hole with heavy mud to 504'. Shot 9 5/8" casing 900, 800 & 700. Pulled 709'(overall) 9 5/8" casing. Filled hole with heavy mud to within 10' of surface. Cemented to top of surface. Set pipe marker and abandoned location. No attempt was made to recover 12 1/2" surface pipe as 200 sacks cement was circulated around same. H. F. Zion Phillips Petroleum Co. Lease Foreman

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn to before me this
16 day of January, 19 42

Geo. D. Henshaw
Geo. D. Henshaw Notary Public

My Commission expires 6-1-43

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position District Superintendent

Representing Phillips Petroleum Co.
Company or Operator

Address Box 6666, Odessa, Texas

Roy Garbrough
Name
OIL & GAS INSPECTOR
Title

