

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction
verse side)Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-13646

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Luzon Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 13, T-24-S, R-35-E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

1. OIL ☐ GAS ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR

Union Oil Company of California

3. ADDRESS OF OPERATOR

P. O. Box 671 - Midland, Texas 79702 U.S. GEOLOGICAL SURVEY

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
See also space 17 below.)
At surface

660' FNL and 1980' FEL

14. PERMIT NO.

30 025 25649

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3428' GR.

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1-24-78 - Spot Plug No. 1 from 14,075' to 13,838' in 6-1/8" open hole with 50 sx cement.
Spot Plug No. 2 from 12,765' to 12,528' in 6-1/8" open hole with 50 sx cement.
Spot Plug No. 3 from 11,926' to 11,659' in 6-1/8" open hole and bottom of 7" OD Casing with 50 sx cement.
- 1-25-78 - Spot Plug No. 4 from 9,680' to 9,406' in 7" OD Casing with 50 sx cement.
Spot Plug No. 5 from 7,198' to 6,924' in 7" OD Casing with 50 sx cement.
Spot Plug No. 6 from 5,375' to 5,101' in 7" OD Casing with 50 sx cement.
Spot Plug No. 7 from 4,150' to 3,876' in 7" OD Casing with 50 sx cement.
- 2-20-78 - Moved in and rigged up casing pulling unit.
- 2-22-78 - Cut off 7" OD Casing at 3,200', pulled and laid down 7" OD Casing.
- 2-23-78 - Ran 2" Tubing to top of Plug No. 7 at 3,694'. Spotted Plug No. 8 from 3,300' to 3,100' in 7" OD Casing stub and 9-5/8" OD Casing with 50 sx cement.
Spot Plug No. 9 from 1,709' to 1,500' in 9-5/8" OD Casing with 100 sx cement.
Spot Plug No. 10 from 50' to surface in 9-5/8" OD Casing with 25 sx cement.
10 ppg mud placed between plugs. Welded 1/2" steel plate on surface casing.
Installed 4" x 4' pipe dry hole marker, as per N.M.O.C.C. rules and regulations.

WELL PLUGGED AND ABANDONED FEBRUARY 23, 1978.

18. I hereby certify that the foregoing is true and correct

SIGNED

J.R. Hughes

TITLE District Drilling Supt.

DATE March 13, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

SEP 8 1978

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; kind or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847 - 488

WENT PLUGGED AND ABANDONED FEBRUARY 23, 1978.

I.R. Hughes, District Director

012 270 08 10 2005 001 002*