

5-USGS-Hobbs

1-File

COPY TO O. G.

1-R.W. Blohm-Midland

1-BWI-MLMU

Form 9-331
Dec. 1973

1-W.A. Frnka-Tulsa

9-WIO's

Form Approved.
Budget Bureau No. 42-R1424

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Water Injection

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Ltr G, 1880 FNL & 1880 FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☒ XXXXFRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/4/80 Ran 11 jts. (491') 8 5/8" OD 24# K-55 ST&C Casing and set @ 502'. FC @ 456'. Western cemented w/150 sxs. Lite, w/2% CaCl, 1/4# Flocele, and 200 sxs. Class "C" Cement w/2% CaCl. Plug down @ 9:15 A.M. Circulated 100 sxs. WOC 18 hrs. Pressured up to 1200# on casing for 30 minutes. OK.

9/10/80 Dresser Atlas ran Dual Laterolog, Micro Laterolog Comp. Density, Comp. Neutron, Gamma Ray. Lay down drill pipe. Ran 3738' (90 jts) 5 1/2" 14# K-55 R-3 Casing "A" Cond. and set @ 3748'. Float Collar @ 3702'. Western cemented w/1100 sxs. of Lite. 10% Salt, 2% CaCl, 1/4# Cello Seal, and 200 sxs. 50-50 Poz w/2% CaCl, 1/4# Cello Seal. Plug down 4:00 A.M. Circ. 10 sxs. WOC

CONTINUED ON BACK

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Supt. DATE 10/1/80APPROVED BY P. Chester TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

OCT 2 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-140

9/11/80 Set slips and released rig 9:00 A.M. TD 3750'; Waiting on completion.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WELL ABANDONMENT REPORT

1. NAME OF OPERATOR
2. NAME OF WELL
3. ADDRESS OF OPERATOR
4. LOCATION OF WELL (SECTION, TOWNSHIP, RANGE)
5. LOCATION OF WELL (COUNTY, STATE)
6. DATE OF OPERATION
7. TYPE OF OPERATION
8. DEPTH TO TOP OF WELL
9. DEPTH TO BOTTOM OF WELL
10. METHOD OF PLACEMENT OF CEMENT PLUGS
11. MUD OR OTHER MATERIAL PLACED BELOW, BETWEEN AND ABOVE PLUGS
12. AMOUNT, SIZE, METHOD OF PARTING OF ANY CASING, LINER OR TUBING PULLED
13. DEPTH TO TOP OF ANY LEFT IN THE HOLE
14. METHOD OF CLOSING TOP OF WELL
15. DATE WELL SITE CONDITIONED FOR FINAL INSPECTION