

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Highland Production Company

3. ADDRESS OF OPERATOR
810 N. Dixie, Suite 202, Odessa, TX 79761

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FEL and 990' FSL
AT TOP PROD. INTERVAL: 660' FEL and 990' FSL
AT TOTAL DEPTH: 660' FEL and 990' FSL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON*

(other) Simple completion information

SUBSEQUENT REPORT OF:

-
-
-
-
-
-
-
-

5. LEASE	LC-068281-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME	Conoco Federal
9. WELL NO.	3
10. FIELD OR WILDCAT NAME	East Mason (Delaware)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Section 19, T-26-S, R-32-E, NMPM
12. COUNTY OR PARISH	Lea
13. STATE	New Mexico
14. API NO.	30-025-29986
15. ELEVATIONS (SHOW DF, KDB, AND WD)	3165.3 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-28-87 Spud 12:00 A.M.

7-29-87 Set 1238' 8-5/8" 24# J-55 ST&C Casing. Cemented with 450 sacks Halliburton Light and 113 lbs. Floecele Mix (1/4 lb. per sack). 200 sacks API Class C cement and 4 sacks Calcium Chloride Mix 2% w/200. Circulated to surface.

8-04-87 Set 4295' 5-1/2" 15.5# LT&C API LTV Casing with 550 sacks light, 250 sacks Class C with Poz Mix A. Did not circulate, top of casing at 500'. BLM man was present and gave O.K. *cmf.*

ACCEPTED FOR RECORD

SJS

AUG 25 1987

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

CARLSBAD, NEW MEXICO

SIGNED *Marvin L. Smith* TITLE President DATE August 17, 1987

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
AUG 31 1987
OCD
HOBBS OFFICE