

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL. E*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <u>Drilling</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>71-034711</u>
2. NAME OF OPERATOR <u>Arch Petroleum Inc.</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>10 Desta Dr., Suite 420 East, Midland, Texas 79705</u>		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>2310 FSL & 660 FWL, Section 35, T23S, R37E unit L</u>		8. FARM OR LEASE NAME <u>Baylus Cade Federal</u>
14. PERMIT NO. <u>Approved 9-29-89</u>		9. WELL NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>3246.2 GR</u>		10. FIELD AND POOL, OR WILDCAT <u>Teague Devonian</u>
		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA <u>Sec 35, T23S, R37E</u>
		12. COUNTY OR PARISH <u>Lea</u>
		13. STATE <u>New Mexico</u>

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Drilling Operations

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Oct 2, 1989: Spud 12 1/4" hole at 8:30 P.M. Drilled to TD at 1170'.

Oct 4, 1989: Ran 29 jts of 8 5/8" 24# casing. Set at 1170'. Cement with 750 sx Class "C" with 2% CaCl and 1/4# per sx Flocele. Plug down at 5:30 P.M. Circulated 114 sx to pit. WOC for 12 hours.

Oct 5, 1989: Tested BOP and casing to 1000# for 30 minutes prior to drilling out from surface casing.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Operations Manager

DATE 10-25-89

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
[Signature] DATE

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO