Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 30-025-31955

RICT II Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504-208

P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lesse STATE FEE X			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.			
SUNDRY NOTICES AND REPORTS ON V (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEL DIFFERENT RESERVOIR. USE "APPLICATION FOR (FORM C-101) FOR SUCH PROPOSALS.)	PEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name			
1. Type of Well: OIL GAS WELL X WELL OTHER				
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.	8. Well No. 8			
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	9. Pool name or Wildcat UNDESIGNATED (WILDCAT)			
4. Well Location Unit Letter _D : 510 Feet From The NORTH	Line and 660 Feet From The WEST Line			
Section 9 Township 23-SOUTH Range 37-EAST NMPM LEA County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3317', KB-3329'				
	te Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB			
OTHER:	OTHER: SPUD & SURFACE CASING X			
12. Describe Proposed or Completed Operations (Clearly state all pertinent detail work) SEE RULE 1103.	s, and give pertinent dates, including estimated date of starting any proposed			
CLASS C W/ 2% CACL2 (14.8 PPG, 1.32 CF/S). PLUG DC 4. NU BOP & TESTED TO 1000#. TESTED CASING TO 1000	T @ 1155'. RAN 9 CENTRALIZERS. GGEL, 2% CACL2 (13.5 PPG, 1.74 CF/S). F/B 200 SACKS DWN @ 9:30 PM 05-26-93. CIRCULATED 15 SACKS. FOR 30 MINUTES FROM 9:45 AM TO 10:15 AM 05-27-93. O 9:45 AM 05-27-93. REQUIREMENTS OF RULE 107, OPTION 2: TAIL 264 (CU.FT).			

6

2. APPROX. TEMPERATURE OF SLURRY WHEN MIXED: 3. EST. FORMATION TEMPERATURE IN ZONE OF INTERE 4. EST. CEMENT STRENGTH AT TIME OF CASING TEST: 5. ACTUAL TIME CEMENT IN PLACE PRIOR TO TESTING:	50°F. ST: 90°F. 1200 PSI.	
. DRILLING 11 INCH HOLE.		
bereby certify that the information above is true and complete to the best of my knowledge SIGNATURE	e and belief. TITLE DRILLING OPERATIONS MANAGER	
THE OR PRINT NAME C.P. BASHAM		TELEPHONE NO. 915-6884620
This space for State Use) (SET SHEET SHEET OF JERMY BY OFFICIAL SET SHEET SHEET SHEET SHEET OPPROVED BY CONDITIONS OF APPROVAL, IP ANY:	TITLE	— ДАТВ — — — — — — — — — — — — — — — — — — —