

OIL CONSERVATION DIVISION

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30 025 32495
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil / Gas Lease	
7. Lease Name or Unit Agreement Name	DAVIS, F. B.
8. Well No.	5
9. Pool Name or Wildcat	N. Teague (Drinkard-Abo, Tubb Associated)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Lease Name or Unit Agreement Name DAVIS, F. B.			
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐				
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.	8. Well No. 5			
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240	9. Pool Name or Wildcat N. Teague (Drinkard-Abo, Tubb Associated)			
4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>NORTH</u> Line and <u>330</u> Feet From The <u>EAST</u> Line Section <u>8</u> Township <u>23-S</u> Range <u>37-E</u> NMPM <u>LEA</u> COUNTY				
10. Date Spudded 9/4/94	11. Date T.D. Reached 9/17/94	12. Date Compl. (Ready to Prod.) 2/15/95	13. Elevations (DF & RKB, RT, GR, etc.) GR-3319', KB-3331'	14. Elev. Csghead
15. Total Depth 7250'	16. Plug Back T.D. 7162'	17. If Mult. Compl. How Many Zones? 2	18. Intervals Drilled By 0' - 7250'	19. Producing Interval(s), of this completion - Top, Bottom, Name 6090' - 6241', Tubb; 6353' - 7010', Drinkard-Abo
20. Was Directional Survey Made YES				21. Type Electric and Other Logs Run DLL-MSFL-DSN
22. Was Well Cored NO				


CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
9 5/8	36#	1180'	12 1/4	550	
7	23#	7250'	8 3/4	3000	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
NONE					2-1/16"	6075'	6303'
					2-3/8"	6369'	

26. Perforation record (interval, size, and number) 6090'-6241', 2 JSPF, 80 HOLES (TUBB) 6353'-7010', 2 JSPF, 168 HOLES (DRINKARD-ABO) The North Teague Tubb Associated is duald with the North Teague Drinkard-Abo	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 6090'-6241' 6353'-7010' 20% HCL flush w/3948g 65q+7400water
--	--

28. PRODUCTION							
Date First Production 10/11/94	Production Method (Flowing, gas lift, pumping - size and type pump) Flow-Flow (Tubb, Drinkard-Abo)					Well Status (Prod. or Shut-in) Producing	
Date of Test 3/20/95-11	Hours tested 24	Choke Size Open-40/64	Prod'n For Test Period	Oil - Bbl. 32-30	Gas - MCF 376-509	Water - Bbl. 27	Gas - Oil Ratio 11750-1696
Flow Tubing Press. 200#-120#	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl. 32-30	Gas - MCF 376-509	Water - Bbl. 27-27	Oil Gravity - API -(Corr.) 45-51.2	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						Test Witnessed By D. E. Welborn	

30. List Attachments DEVIATION SURVEY	
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.	
SIGNATURE 	TITLE Engineering Assistant
DATE 4/3/95	Telephone No. 397-0426
TYPE OR PRINT NAME Darrell J. Carriger	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1113	T. Canyon
T. Salt	1215	T. Strawn
B. Salt	2467	T. Atoka
T. Yates	2610	T. Miss
T. 7 Rivers	2960	T. Devonian
T. Queen	3321	T. Silurian
T. Grayburg	3657	T. Montoya
T. San Andres	4018	T. Simpson
T. Glorieta	5035	T. McKee
T. Paddock	5240	T. Ellenburger
T. Blinebry	5567	T. Gr. Wash
T. Tubb	6089	T. Delaware Sand
T. Drinkard	6304	T. Bone Springs
T. Abo	6613	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 6089 to 6304
No. 2, from 6304 to 7250

No. 3, from to
No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1113	1113	REDBEDS				
1113	1215	102	ANHYD.				
1215	2467	1252	SALT, ANHYD., SHALE				
2467	2610	143	ANHYD., SALT, DOL.				
2610	2960	350	SNDSTNE., ANHYD., DOL.				
2960	3321	361	DOL., SNDSTNE.				
3321	3657	336	SNDSTNE., DOL.				
3657	4018	361	DOL, SNDSTNE				
4018	5035	1017	DOL, ANHYD.				
5035	5240	205	DOL.				
5240	5567	327	DOL., ANHYD.				
5567	6089	522	DOL., ANHYD.				
6089	6304	215	SNDSTNE., DOL.				
6304	6613	309	DOL., ANHYD.				
6613	7250TD	637	DOL., ANHYD., SHALE				