Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

_	NS. COMMISSION	
W.M. UIL COL BOX 19	NS. CO REPAI	
O. BUNNE	NEX FORM APPROVED Budget Bureau No. 1004-01: Expires: March 31, 1993	

BUREAU OF LAND MANAGEMENT		5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS		NM- 6905 69605
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well		· ·
X Oil Gas Well Other		8. Well Name and No.
2. Name of Operator YATES PETROLEUM CORPORATION	(505) 7/0 1/71)	Ed Powell Unit #1
YATES PETROLEUM CORPORATION (505) 748-1471) 3. Address and Telephone No.		9. API Well No.
105 South 4th St., Artesia, NM 88210		30-025-33482 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Wildcat Abo
1250' FSL & 900' FEL of Section 20-T26S-R38E (Unit P, SESE)		11. County or Parish, State
		Lea Co., NM
CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPOR	
TYPE OF SUBMISSION	TYPE OF ACTION	
L_ Notice of Intent	Abandonment Recompletion	Change of Plans
X Subsequent Report	Plugging Back	New Construction Non-Routine Fracturing
	Casing Repair	Water Shut-Off
L_J Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Intermediate casing &	Dispose Water (Note: Report results of multiple completion on Well
Describe Proposed or Completed Operations (Clearly state a)	cement I pertinent details, and give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Line form)
Bive appariance locations and measured and time vento	al depths for all markers and zones pertinent to this work.)*	
4230'. Cemented with 1025 sa 1/4#/sack celloseal (yield 2. 1.32, weight 14.8). PD 4:00 sacks. WOC. Nippled up and	AM 6-11-96. Ran 104 joints of 8-5/8' at 4272'. Float shoe set at 4272'. cks BJ Lite (65-35-6), 10#/sack salt, 06, weight 12.7). Tailed in with 500 AM 6-12-96. Bumped plug to 1650 psi, tested BOP's to 3000 psi and hydril to 35 hours. Reduced hole to 7-7/8". Re	Float collar set at 5#/sack gilsonite and sacks Class C (yield OK. Circulated 291
)	ACCEPTED FOR RECOMMENDED FOR RECOMMEND AND ASSESSED FOR RECOMMEND AND ASSESSED FOR RECOMMEND ASSESSED FOR RECOMMEN	
Signed Signed (This space for Federal or State office use)	Operations Technician	Date June 26, 1996
Approved by	Tide	Date