

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

TEXACO Exploration & Production Inc.

3. Address and Telephone No.

P.O. Box 3109 MIDLAND, TX 79701-6881/4438

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UNIT LETTER H, 2310 FEET FNL, 660 FEET FEL,
SECTION 35, TOWNSHIP 24S, RANGE 37E

5. Lease Designation and Serial No.

UM-11218

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. C.C. Feistoe

B-FEDERAL NCT2-6

9. API Well No.

30-025-11363 k

10. Field and Pool, or Exploratory Area

JUSTIS TUBB DEINKAED

11. County or Parish, State

LEA, NEW MEXICO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent
 Subsequent Report
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment **DHC**
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other
 Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut-Off
 Conversion to Injection
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

*Circ 9.5" 35 VISC. MUD
BETWEEN CMT PLUGS

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. SET CIBP IN NORTH (BLINEBEY) ± 5400, FILL 2 7/8" CSQ w/ CMT 5400'-3180'. "C" CMT 70 SXS.
2. SET CIBP IN WEST (TUBB DEINKAED) ± 5900, FILL 2 7/8" CSQ w/ CMT 5900'-3180'. "C" CMT 75 SXS
3. SET CIBP IN EAST (FUSSELMAN) ± 6900, FILL 2 7/8" CSQ w/ CMT 6900'-3180'. "C" CMT 100 SXS.
4. CUT 3 STRINGS CSQ, LID 2 STRINGS. SPOT 40 SX PLUG 3180-3080. Tag
5. SPOT 40 SX PLUG 2400-2300'
6. PERF & SQUEEZE 60 SX PLUG 1100-900'
7. PERF & SQUEEZE 100 SX PLUG 330-200.
8. 10 SX SURF INSTAN DRY HOLE MARKER

14. I hereby certify that the foregoing is true and correct

Signed

G. T. Collett

Title

PROCTOR ENGINEER

Date

(This space for Federal or State office use)

(ORIG. SGD.) GARY GOURLEY

Title

Date

2/3/00

Approved by
Conditions of approval, if any:

GWW/PW

