

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 3002511401
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2657
7. Lease Name or Unit Agreement Name State A-2
8. Well No. 1
9. Pool name or Wildcat Langlie Mattix SR-QN-GR
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3127' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

2. Name of Operator  
Conoco Inc.

3. Address of Operator  
10 Desta Dr. Ste 100W, Midland, Tx 79705

4. Well Location  
Unit Letter 0 : 660' Feet From The South Line and 1980' Feet From The East Line  
Section 2 Township 25S Range 37E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to Plug & Abandon the State A-2 No. 1 well as follows:

- GIH w/ bit & scraper to 3020'.
- RIH w/ 7" cmt ret & 2 3/8" workstring to 3006'.
- Squeeze existing perms @ 3056-3150' w/30 sx cmt w/5 sx Class "C" cmt on top of retainer @ 3006'.
- RIH w/ 2 3/8" workstring to 341' & pump 20 sx of Class "C" cmt.  
NOTE: Plug is to be set a minimum of 50' below & 50' above csg shoe @ 391'.
- RIH w/ 2 3/8" workstring to 160' & pump 30 sx Class "C" cmt to fill up 7" csg. to the surface.  
NOTE: Plug is to be at least 50' but not less than 25 sx of cmt. The top of the plug shall be placed as near the eventual csg cut off point as possible.
- Cut off csg strings at base of cellar or 3' below final restored ground level.
- Cover wellbore with metal plate at least 1/4" thick, welded in place or a cement cap extending at least 12' beyond the 10 3/4" surf csg & at least 4' thick.
- Erect abandonment marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Hoover TITLE Sr. Conservation Coordinator DATE 08-28-92  
TYPE OR PRINT NAME Jerry W. Hoover (915) 686-6548 TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE AUG 31 '92

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
AUG 31 1992  
JGD HOBBS OFFICE