

N.

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

APR 25 1945

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

**Amerasia Petroleum Corporation, Drawer D, Monument, New Mexico.**

Company or Operator

Address

Ida Wimberly

Well No. 1

in NE 1/4 NE 1/4

of Sec. 26

T. 25S

Lease

R. 37E

N. M. P. M.

Langlie

Field, Lea

County.

Well is 660 feet south of the North line and 660 feet west of the East line of Section 26-25S-37E

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Ida Wimberly Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced March 20, 1945 Drilling was completed April 16, 1945

Name of drilling contractor Two States Drilling Co. Address Dallas, Texas

Elevation above sea level at top of casing 3068 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10 3/4	29	Slip Joint Weld	216'	Set Shoe				
7 5/8"	17.9	Slip Jt. Weld	1074'	Float				
5 1/2"	15.5	8 Seam	2935'	Float				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 3/4 10 3/4		216'	175	Halliburton		
9 5/8 7 5/8		1074'	250	Halliburton		
6 3/4 5 1/2		2935'	250	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	None					

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 5230 feet, and from feet to feet

Cable tools were used from 56 feet to feet, and from feet to feet

## PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours 3,587,000 Gallons gasoline per 1,000 cu. ft. of gas Dry

Rock pressure, lbs. per sq. in. 1200

## EMPLOYEES

A. N. Wood Driller G. R. Robinett Driller

H. A. Wigley Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 23rd Monument, New Mexico. April 23, 1945

day of April 1945 Name

Will Hale Taylor Notary Public Position Asst. Dist. Supt.

My Commission expires Address Representing Amerasia Petroleum Corporation

Drawer D, Monument, New Mexico.

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	40	40	Caliche and Red Bed
40	48	8	Red Bed
48	56	8	Red Rock
56	112	56	Red Rock and Red Bed
112	175	63	Red Bed and Sand
175	223	48	Surface Rock
223	300	77	Red Rock and Red Bed
300	330	30	Hard Sand
330	510	180	Sand
510	615	105	Red Bed and Shells
615	622	7	Red Rock
622	850	228	Red Bed and shells
850	930	80	Anhydrite
930	1040	110	Broken Anhydrite
1040	1121	81	Potash
1121	1160	39	Anhydrite and Potash
1160	1282	102	Salt
1282	1475	213	Salt and Anhydrite
1475	1809	334	Anhydrite and Salt
1809	2140	331	Salt and Anhydrite
2140	2160	20	Gypsum and Anhydrite
2160	2200	40	Anhydrite and Gypsum
2200	2370	170	Anhydrite and Lime
2370	2415	45	Lime and Anhydrite
2415	2537	122	Anhydrite and lime
2537	2560	23	Lime and Anhydrite
2560	2599	39	Anhydrite and Lime
2599	2630	31	Lime and Anhydrite
2630	2980	350	Lime
2980	3230	250	Lime
3230			Total Depth

## GEOLOGICAL TOPS

Elevation	3076' Derrick Floor,
	3068' Top of Casing
Base Red Beds	880'
Top of Salt	1180'
Base of Salt	2145'
Zone #1	2345'
Stuart Sand	2950-3044
Penrose Sand	3072-3218'