Form 9-331 a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY -

Land Offic	ws it.	exic	0
Lease No.	LC-0	325	10(6)
Unit	- <b>A</b>		

1

## SLINDRY NOTICES AND DEDO

NOTICE OF INTENTION TO DRILL  NOTICE OF INTENTION TO CHANGE PLANS	
	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	ALIERING CASING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	THE DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING.	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	2-27 , 192
Well No. 1-35 Fed is located 36 ft. from	$\{ \begin{bmatrix} N \\ S \end{bmatrix} $ line and $\{ \begin{bmatrix} S \\ S \end{bmatrix} $ line of sec. $\{ \begin{bmatrix} S \\ S \end{bmatrix} \end{bmatrix}$
(½ Sec. and Sec. No.) (Twp.)	OPELIATIONS BY:
(Twp.)	(Range) (Meridian) 0. 3. 0. 0. N file
Justis (Field) (County	or Subdivision) - News 100 0. ATTACHED
	5 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
The elevation of the derrick floor above sea le	vel i3034 ft. The street armoned
	- 1
	ILS OF WORK
otate names of and expected depths to objective sands; show size ing points, and all c	zes, weights, and lengths of proposed casings; indicate mudding jobs, cement—other important proposed work)
12 1/4" hole to approx 1000' 8 3/4" hole to approx 5800'	and set 9 5/69 casing with 400 sks. and set 7" casing with 750 sks.
12 1/4" hole to approx 1000' 8 3/4" hole to approx 5000' Commt on the 9 5/3" casing must be of the salt section on the 7" casing lunderstand that this plan of work must receive approval in the 1000' casing the salt section on the 1000' casing the salt section of the 1000' casing the 1000'	and set 9 5/67 casing with 400 sks. and set 7 casing with 750 sks. circulated and returned to above the base g. writing by the Geological Survey before operations may be commenced.
12 1/4" hole to approx 1000' 8 3/4" hole to approx 5800' Cement on the 9 5/8" casing must be of the salt section on the 7" casing	and set 9 5/67 casing with 400 sks. and set 7" casing with 750 sks. circulated and returned to above the base g. writing by the Geological Survey before operations may be commenced.

7/10£