

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
N. M. STATE LAND TRUST DIVISION
P.O. BOX 1980
ROSWELL, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. 83240NM 19623	
2. NAME OF OPERATOR HNG OIL COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 2267, Midland, Texas 79702		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1880' FWL		8. FARM OR LEASE NAME Vaca 13 Federal	
14. PERMIT NO. -		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3360.6' GR		10. FIELD AND POOL, OR WILDCAT Wildcat Morrow	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T25S, R33E	
		12. COUNTY OR PARISH Lea	13. STATE NM

RECEIVED
AUG 23 11 28 AM '83

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF: 8/12/83	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <u>Casing test & cement job.</u> <input checked="" type="checkbox"/>	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-13-83 - Set 5050 feet of 9-5/8" 36 & 40 # K-55 ST&C, & 40# K-55 LT&C, Circ. to surface. Cemented with 2000 sacks pacesetter lite C + 1/4#/sack cello-seal, 12.7 ppg. And 475 sacks Class C cement + 3#/sack salt + 1/4#/sack Cello-Seal, 14.8 ppg. 30 minutes pressure tested to 1700#. WOC - 18 hours.

18. I hereby certify that the foregoing is true and correct
SIGNED Betty Gildon TITLE Regulatory Analyst DATE 8/22/83
Betty Gildon
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
AUG 26 1983

*See Instructions on Reverse Side

RECEIVED
AUG 30 1983
O.C.D.
HOBBS OFFICE