

# DRILLING PLAN

Attach to BLM Form 3160-3  
ARCO Oil and Gas Company  
Well: South Justis Unit G-190  
Section 24-T25S-R37E  
1090' FNL & 2455' FEL  
Lea County, New Mexico

## 1. Surface Geological Formation

Ogallala Formation of late Tertiary age.

## 2. Estimated Tops of Geological Markers

<u>Formation</u>	<u>TVD</u>
Salt	1000'
Yates	2275'
Queen	2975'
Grayburg	3100'
San Andres	3550'
Glorietta	4625'
Blinebry	5000'
Tubb	5675'
Drinkard	5875'

## 3. Estimated Tops of Possible Water, Oil, Gas or Minerals:

Sands above 1000'	Water *
Yates	Gas**
Blinebry	Oil or Gas**
Tubb	Oil or Gas**
Drinkard	Oil or Gas**

\* Groundwater will be protected by 8-5/8" surface casing cemented to surface.

\*\* Productive horizons will be protected by 4-1/2" production casing cemented to surface.

## 4. Pressure Control Equipment

Interval, TVD  
0' - 1000'

Pressure Control Equipment  
No pressure control required

1000' - 6200'

11", 3M psi double ram preventer with 3M psi annular preventer.

Exhibits 1, 2, and 3 show the BOP stack arrangement, the choke manifold arrangements and the BOP specifications, respectively. The BOPE will be hydraulically tested per BLM requirements outlined by Onshore Oil and Gas Order No. 2. Pipe rams and blind rams will be functioned on each trip out of the hole. The annular preventer will be functioned once a week. All BOPE checks and tests will be witnessed by ARCO's representative and will be noted on the IADC daily drilling report. Accessories to BOPE will include an upper kelly cock, lower kelly cock, and floor safety valve all with pressure rating equivalent to the BOP stack.

**RECEIVED**

**APR 06 1993**

**OCD HOBBS OFFICE**