

(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

032096 (10)

Lease No.

N.M.P.U.

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Lockhart A-17 #4

Hobbs, New Mexico

November 29, 1949

Well No. 4 is located 660 ft. from $\begin{matrix} N \\ S \end{matrix}$ line and 660 ft. from $\begin{matrix} E \\ W \end{matrix}$ line of sec. 17

NE 1/4 Section 17

21-S

37-E

N.M.P.M.

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Drinkard

Lea

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 3495 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Subject well was drilled to 6770' in Lime. On 11-8-49 set 7" OD casing at 6769' and cemented with 650 sacks, using 11 centralizers and 107 scratchers.

On 11-18-49 found 32' cement inside 7" casing. Tested for 30 minutes with 1200 p.s.i. pressure, drilled plug to 6770' and tested for 30 minutes with 1200 p.s.i. pressure. No drop in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Continental Oil Company

Address

Box CC

Hobbs, New Mexico

By

Title

District Superintendent