Distance 1000000000000000000000000000000000000		o Appropriate District	State	of New Me	xico	Form C-103			
District (-179) 78-128 OIL CONSERVATION DIVISION 30-025-23896 District (-169) 74-128 Stat Field, Area is Marking 1220 South St. Francis Dr. Stat Field, Area is Marking Santa Fe, NM 87505 5. Indicate Properties (-179) 64-128 Detert (-169) 74-560 Santa Fe, NM 87505 6. State Oil & Cal Lease No. E205.51 Field (-169) 74-560 Santa Fe, NM 87505 7. Lease Name or Unit Argement Name (-160) 7400 7500 7500 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 761 760 760 760 760 760 760 760 760 760 760	Office District I – (575) 393-6161 Energy, Minerals and Natural Resources								
3115 First S., Areas, NM 38210 DID CONSERVATION DIVISION 3115 First S., Areas, NM 38210 1220 South SL Francis Dr. 2006 SLT - (000 Areas) Santa Fe, NM 87505 2020 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 2020 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 2020 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 203 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 203 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 203 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 203 S. Frence Dr., Seat Fe, NM F. Tease Name or Unit Agreement Name 204 S. The of Vell: Oil Well G as Well Other Obe (00/03/2016 2. Name of Operator RECEIVED V 9. OGRID Number 2. Name of Operator NMEX Exception VIL RUGE MORROW 4. Well Location In Elevation (Show whether DR, RKP, RT, GR, etc.) OXI RUGE MORROW 4. Well Location I. Elevation (Show whether DR, RKP, RT, GR, etc.) STO'G GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL WORK A DVID AND AND AND AND AND AND AND AND AND AN					DIVISION				
1000 Robers R. Amer., NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lase No. 1020 Robers R., MM E-78234 1020 Robers R., Sama Fe, NM E-78234 1020 Robers R., Sama Fe, NM C. State Oil & Gas Lase No. 1020 Robers R., Sama Fe, NM E-78234 1020 Robers R., Sama Fe, NM C. D. = Hold District Control (Control Control Control (Control Control Control (Control Control Control (Control Control (Control Control (Control Control (Control Control (Control (Contro (Control (Control (Control (Control (Control (Control (Control (C	811 S. First St., A	rtesia, NM 88210							
1220 5.8. Function Dr., Sama Fe, NM E-7824 17935 SUNDRY NOTCES AND REPORTS ON WELLS Image: Control of the second of						· · · · · · · · · · · · · · · · · · ·			
\$755 SUNDRY NOTICES AND REPORTS ON WELLS ON OT USE THIS FORM FOR PROFOMENTS ON WELLS ON OT USE THIS FORM FOR PROFOMENTS ON WELLS ON OT USE THIS FORM FOR PROFOMENTS ON WELLS OD OT USE THIS FORM FOR PROFOMENTS ON THE PROFOMENTS OD OT USE THIS FORM FOR PROFOMENTS ON THE PROFOMENTS OD OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTHER OTH	<u>Bisite(11</u> (565) 410-5100					6. State Oil &			
DO NOT USE THIS FORM FOR PROCESALS TO DERLL OR TO DEEPEN OR PLUG MACK TO A DIFFERENT ESSENVOL. USE APPLICATION ROF REMIT (FORM CHIDTON SUCE PROCESALS) LEA ED STATE (NCT-A) 1. Type of Well: Oil Well Gas Well ⊠ Other O(G)3/2016 8. Well Number 2 2. Name of Operator AMTEX ENERGY, INC. 9. OGRID Number 785 3 3. Address of Operator ID. Pool name or Wildcat OUALL RIDGE MORROW 4 4. Well Location Unit Letter, K.; 1980. feet from theSouth line and1920. feet from theWestline Vest Inc Section 10. Pool name or Wildcat OUALL RIDGE MORROW 4 4. Well Location 11. Elevation (Show whether DR, RKB, RT; GR, etc.) 3770' GR 10. Pool name or Wildcat SUBSEQUENT REPORT OF: FERFORM REPOLAL WORK PLANS DE PLANS DE PLANS DOWNHOLCE OF INTENTION TO: PERFORM REPOLAL WORK PLATERING CASING									
PROFORALS OCD - HOBBS 8. Well Number 2 1. Type of Well: Oil Well Gas Well Z) Other 06/03/2016 8. Well Number 2 2. Name of Operator AMTEX ENERGY, INC. 785 7 3. Address of Operator 10. Pool name or Wildcat 0UAIL RIDGE MORROW 4. Well Location Unit Letter_K : 1980 feet from the South line and 1980 feet from the West line Section 16 9. OGRID Number 785 4. Well Location 11. Elevation Ghow whether DR, RR, RT, GR, etc.) 9. MPM LEA County 786 700 GR 11. Elevation Ghow whether DR, RR, RT, GR, etc.) SUBSEQUENT REPORT NG: REMEDIAL WORK ALTERIOR CASING	(DO NOT USE T					7. Lease Name	e or Unit Agreement N	ame	
1. Type of Well: Oil Well □ Gas Well ☑ Other 06/03/2016 8. Well Number 2 2. Name of Operator RECEIVED 9. OGRID Number 3. Address of Operator P.O. BOX 3418, MIDLAND, TX 79702 10. Pool name or Wildcat 4. Well Location Unit Letter K: 1980, feet from the <u>South</u> line and 1980, feet from the <u>West</u> line OUAIL RIDGE MORROW 4. Well Location 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF; PERFORM REMEDIAL WORK ALTERING CASING COMMENCE DALLING OPNS.] PAND A DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS.] PAND A CASING/CEMENT JOB OTHER: OTHER: No 5C CSG Image of the data, and give pertinent dates, including estimated date of starting any proposed or completion. OTHER: Run 5.5' CSG Liner Inside 7.25' CSG 13. Describe proposed or completion. Cleaning, Drifting and Tally Casing. Alt Her Work 6.7'S' Bit to 10,000' Starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completions. 14. Hold 15 min. Safety Meeting X Cu-off Bolts and Remove Oid Wellhead X deliver tubing, put on racks. Alt Held 15 min. Safety Meeting X Cu-off Bolts and Remove Oid Wellhead X deliver tubing, put on racks.	DIFFERENT RE			FORM C-101) FC	OR SUCH	LEAEL) STATE (NCT-A)	\checkmark	
2. Name of Operator 2 AMTEX ENERGY, INC. RECEIVED 9. OGRID Number 785 785 3. Address of Operator 10. Pool name or Wildcat 0. Unit Letter _K : 1980 feet from the South line and 1980 feet from the West line 9. OGRID Number 4. Well Location 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL COMMENCE DRILLING OPNS PAND A CHANGE PLANS ALTERING CASING CASING/CEMENT JOB OWNHOLE COMMINGLE DESCRIPTION TO: REMEDIAL WORK PLUG AND ABANDON CHANGE PRILLING OPNS PAND A PAND A PAND A CHANGE DRILLING OPNS PAND A PAND PAND P						8. Well Numb		\checkmark	
2. Address of Operator 785 3. Address of Operator 10. Pool name or Wildcat 9. OLAL RIDGE MORROW 0UAL RIDGE MORROW 4. Well Location 0. Dot 23418. MIDLAND, TX 79702 0. OUAL RIDGE MORROW 4. Well Location 0. Explore the south line and 1980 feet from the West line Section 16 0. OUAL RIDGE MORROW 9. October 1.1 Elevent of the south line and 1980 feet from the West line Section 16 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3. Address of Operator 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF; PERFORM REMEDIAL WORK PLUG AND ABANDON ChANNE PLUL OR ALTER CASING ALTERING CASING OWNHOLE COMMINGLE 0. MULTIPLE COMPL COMMENCE DRILLING OPNS.] PAND A 13. Describe proposed or completed operations. (Clearly state all pertinent dealis, and give pertinent dates, including stimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Meeting x Spend day Cleaning. Drifting and Tally Casing. 1. Hold 15 min. Safety Meeting x Statel Meeting x 17.16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10.205' (Top of 5"' Liner y Actic. Hole Clean w440 Bis Fresh Wate:. <td></td> <td></td> <td></td> <td>00/0</td> <td></td> <td>9 OGPID Nu</td> <td></td> <td></td>				00/0		9 OGPID Nu			
3. Address of Operator [0. POI name or Wildcat 4. Well Location OUAIL RIDGE MORROW 4. Well Location Unit Letter_K.: 1980_feet from theSouth_ line and1980_feet from theWestline Section 16 Township 198 Range 34E NMPM LEA County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS P AND A PULL OR ALTER CASING CHANGE PLANS COMENCE DRILLING OPNS P AND A CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL COMENCE DRILLING OPNS P AND A CASING/CEMENT JOB DOWNHOLE COMMINDE COMENCE DRILLING OPNS P AND A CASING/CEMENT JOB Commence and the of stating any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. Stath Welling X tort of Biots and Remove Old Wellheed X deliver tubing, put on racks. 4. Hold 15 min Safety Meeting X POH W 6.75" Bit tal down thg x Run Collar, 11 c.55" CSG, Float Collar, 11 c.55" CSG S Tost Linegh of 10.205' (Tog of 5'' Liner back to Surface) inside of the 7.625" Casing (10 of 5'' Liner back to Surface) inside of the 7.625" Casin	2. Name of O	-	ENERGY, INC.	iii.o		9. OOKID I <u>N</u> u		\checkmark	
4. Well Location Unit Letter_K.: <u>1980</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>West</u> line Section 16 Township 19S Range 34E NMPM LEA County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR II. Elevation (Show whether DR, RKB, RT, GR, etc.) II. Elevation (Show whether DR, RKB, RT, GR, etc.) SUBSEQUENT REPORT OF: REMEDIAL WORK PLIC AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK PLIC RAITERNS CASING COMENCE OF INTERNTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLIC RAITERNS CASING COMENCE OF INTERNTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PAND A CASING PANDON COMMENCE COMMINGLE COMENCE COMMINGLE COMENCE COMMINGLE COMENCE COMMINGLE OTHER: Run 5.5' CSG Liner inside 7.625' CSG OTHER: OTHER: Run 5.5' CSG Liner inside 7.625' CSG ID OTHER: Run 5.5' CSG Liner inside 7.625' CSG OTHER: OTHER: Run 5.5' CSG Liner inside 7.625' CSG II. Hold 15 min Safety Meeting x Spend day Cleaning. Drifting and Tally Casing. II. Hold 15 min Safety Meeting x Spend day Cleaning. Drifting and Tally Casing. A Hold 15 min Safety Meeting x Cut- GH BOLEs and Remove Old Wellhead x deliver tubing, put on racks. II. Hold 15 min Safety Meeting x Spend day: Cleaning. Drifting and Tall'2 Casing Co	3. Address of					10. Pool name or Wildcat			
Unit Letter K.: 1980 feet from the West line Section 16 Township 198 Range 34E NMPM LEA County 11. Elevation (Show whether DR, RR, RT, GR, etc.) 3770' GR II. III. IIII. IIII. III. IIII. IIII. IIII. IIII. IIII. IIII. IIII. IIII. IIIII. IIIII. IIIII. IIIII. IIIIII. IIIIII. IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII			X 3418, MIDLAND, 7	TX 79702		QUAIL RIDGE MORROW			
Section 16 Township 198 Range 34E NMPM LEA County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770' GR 3770' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK CHANGE PLANS Converted and an operations SUBSEQUENT REPORT OF: PULL OR ALTER CASING MULTIPLE COMPL COMMENCE DRILLING OPNS. P AND A DOWNHOLE COMMINGE MULTIPLE COMPL CASING/CEMENT JOB P AND A CLOSED-LOOP SYSTEM OTHER: Run 5.5' CSG Liner Inside 7.625' CSG Image: CSG Liner Inside 7.625' CSG Image: CSG Completion of the Commpletion of the Common the Commpletion									
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3770 ° GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHARGE PLANS DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM DIG AND ABANDON CHARGE PLANS DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM DIG AND ABANDON CHARGE PLANS DOWNHOLE COMMINGLE COTHER: Run 5.5' CSG Liner inside 7.825' CSG OTHER: Run 5.6427 Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 1. Hold 15 min Safety Meeting x Shend day Cleaning. Drifting and Tally Casing. 2. Hold 15 min Safety Meeting x Install New 11' 5M x 7-11/6' 5M Bolted Back on WH x install BOP x RIH w/ 6.75'' Bit to 10,205' (Top of 5'' Liner) x Circ. Hole Clean w/ 440 Bi5 Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75'' Bit x ad own ty, x Run Collar, 1 jt. 5.5'' CSG, Float Collar, 1 jt. 5.5'' CSG x Total length of 10,205' of 5.5'', 17#, N-80, 8rd, LTC Casing (Top of 5'' Liner back to Surface) inside of the 7.625' Casing. 6. Cement Specialist LLC,								\checkmark	
3770' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS DULL OR ALTER CASING MULTIPLE COMPL DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS PLUL OR ALTER CASING MULTIPLE COMPL DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS COSED-LOOP SYSTEM OTHER: Run 5.5' CSG Liner inside 7.825' CSG OTHER: OTHER: Run 5.5' CSG Liner inside 7.825' CSG 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 2. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min. Safety Meeting x Stard FOB tools and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Stard FOB tools and Remove Old Wellhead x deliver tubing, put on racks. 5. Hold 15 min. Safety Meeting x Stard BOB stard Meetax 6. Cement Specialist LLC, RU x	Secti	on 16					LEA County		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON IEMPORARILY ABANDON CHANGE PLANS OMLLOR ALTER CASING MULTIPLE COMPL DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS OTHER: MULTIPLE COMPL DOWNHOLE COMMINGLE OTHER: Run 5.5° CSG Liner inside 7.825° CSG OTHER: OTHER: Run 5.5° CSG Liner inside 7.825° CSG OTHER: OTHER: Run 5.5° CSG Liner inside 7.825° CSG 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or recompletion. 1. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 2. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing. 5. Hold 15 min. Safety Meeting x NDH W I''SM X - YI/16° SM Bolted Back on WH x install BOP x RIH w/ 6.75° Bit to 10,205° (Top of 5° Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. 6. Cement Specialist L/C, RU x Pump at 2 BPM, Lead – 187 Bbls, 11.6# 50/50-H; and Tail-27 Bbls, 12.0#,	1912年の時代に認識していた。1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915年の1915								
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS DATERIUNG COMMENCE DRILLING OPNS. PAND A DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DATE DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB THER: OTHER: Run 5.5° CSG Liner inside 7.625° CSG CASING/CEMENT JOB OWNHOLE COMMINGLE OTHER: Run 5.5° CSG Liner inside 7.625° CSG CASING/CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min Safety Meeting x Dend and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 5. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. <									
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS DATERIUNG COMMENCE DRILLING OPNS. PAND A DULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DATE DOWNHOLE COMMINGLE COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB THER: OTHER: Run 5.5° CSG Liner inside 7.625° CSG CASING/CEMENT JOB OWNHOLE COMMINGLE OTHER: Run 5.5° CSG Liner inside 7.625° CSG CASING/CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min Safety Meeting x Dend and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 5. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. <	12. Check Appropriate Box to Indicate Nature of Notice. Report or Other Data								
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CHANGE PLANS COMMENCE DRILLING OPNS. PAND A COMMENCE COMMINGLE CASING/CEMENT JOB CASING/CEMENT JOB DOWNHOLE COMMINGLE OTHER: Run 5.5" CSG Liner inside 7.625" CSG CASING/CEMENT JOB OTHER: OTHER: Run 5.5" CSG Liner inside 7.625" CSG CASING/CEMENT JOB OTHER: OTHER: Run 5.5" CSG Liner inside 7.625" CSG CASING/CEMENT JOB OTHER: OTHER: Run 5.5" CSG Liner inside 7.625" CSG CASING/CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion. 1. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. Starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed work). SEE RULE Weeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min Safety Meeting x Intel New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,0205' (Top of 5" Liner) back to Surface) inside of the 7.625" Casing.									
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB CASING/CEMENT JOB OWNHOLE COMMINGLE COMMENCE DRILLING OPNS P AND A CLOSED-LOOP SYSTEM OTHER: OTHER: Run 5.5" CSG Liner inside 7.625" CSG Image: Comment of the completion of the completion or recompletion. 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Mtg. x MIRU Pulling Unit x Truck in and unload 215 jts, 5.5" casing. A Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. Hold 15 min. Safety Meeting x Intel New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10.205 (Top of 5" Liner x Circ. Hole Clean w/ 440 Bbls Freesh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205 of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LC, RU x Pump at 2 BPM, Lead – 187 Bbls, 11.6# 50/50-H, and Tail-27 Bbls, 12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x S									
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE OTHER: OTHER: OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 2. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellheadx deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellheadx deliver tubing, put on racks. 4. 4. Hold 15 min. Safety Meeting x number of the start and unload 215 jts, 5.5" casing. 2. 5. Hold 15 min. Safety Meeting x number of the start and unload 215 jts, 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205" of 5.5", 17#, N=80, 8rd, LTC Casing (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205" of 5.5", 17#, N=80, 8rd, LTC Casing (Top of 5" Liner) back to Surface. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls, 11.6# 50/50-H, and Tail-27 Bbls, 12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top wich 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x W									
CLOSED-LOOP SYSTEM OTHER: OTHER: Run 5.5" CSG Liner inside 7.625" CSG 13. Describe proposed or completed operations. (Clearly state all perinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Mtg. x MIRU Pulling Unit x Truck in and unload 215 jts, 5.5" casing. . 2. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. . 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. . 5. Hold 15 min. Safety Meeting x Cut-off Bolts and Awar the x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205" Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x tay down thg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205" of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls, 11.6# 50/50-H, and Tail-27 Bbls, 12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 Thereby certify that the information above is true and complete to the best of my knowledge and belief.									
OTHER: Image: Construct of the proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Mtg. x MIRU Pulling Unit x Truck in and unload 215 jts, 5.5" casing. 2. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down thg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Ogen: President DATE 10/10/2015 Type or print name William J: Savage WWWWW AutWWWW <td>DOWNHOLE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	DOWNHOLE								
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Meeting x MIRU Pulling Unit x Truck in and unload 215 jts, 5.5" casing. 2. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x install New 11" 5M x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7,625" Casing. 6. Cernent Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Ogenative perting Savage Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips and Date: 09-30-		OP SYSTEM		-			- 7 695" 000		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 2. Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 5. Hold 15 min. Safety Meeting x Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG, Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 OHATE									
1. Hold 15 min. Safety Mtg. x MIRU Pulling Unit x Truck in and unload 215 jts, 5.5" casing. 2. Hold 15 min. Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. 3. Hold 15 min. Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. 4. Hold 15 min. Safety Meeting x install New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE									
 Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. Hold 15 min. Safety Meeting x install New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWW A. August TIPLE President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 Petroleum Engineer 06/03/2016 APPROVED BY: Maark TITLE DATE DATE 									
 Hold 15 min Safety Meeting x Spend day Cleaning, Drifting and Tally Casing. Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. Hold 15 min. Safety Meeting x install New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls, 11.6# 50/50-H, and Tail-27 Bbls, 12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWW A. August TIPLE President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Market, TITLE DATE DATE 	. 1	Hold 15 min Safe	ty Mto y MIDI Dulli	ng Unit v Tru	ck in and unload 21	5 its 5 5" casino	r		
 Hold 15 min Safety Meeting x Cut-off Bolts and Remove Old Wellhead x deliver tubing, put on racks. Hold 15 min. Safety Meeting x install New 11" SM x 7-1/16" SM Bolted Back on WH x install BOP x RIH w/ 6.75" Bit to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. Cernent Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWWM Automation above is true and complete to the best of my knowledge and belief. SIGNATURE William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Matching J. Matching TITLE									
to 10,205' (Top of 5" Liner) x Circ. Hole Clean w/ 440 Bbls Fresh Water. 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Mutuat	3.	Hold 15 min Safet	ty Meeting x Cut-off E	Bolts and Rem	ove Old Wellhead	k deliver tubing,		·	
 5. Hold 15 min. Safety Meeting x POH w/ 6.75" Bit x lay down tbg. x Run Collar, 1 jt. 5.5" CSG, Float Collar, 1 jt. 5.5" CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWW A Surface E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Macute TitLE DATE DATE 	4.						nstall BOP x RIH w/ 6	5.75" Bit	
CSG x Total length of 10,205' of 5.5", 17#, N-80, 8rd, LTC Casing (Top of 5" Liner back to Surface) inside of the 7.625" Casing. 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WILLIAM ALL ALL President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Macude TITLE DATE DATE	5						CSG. Float Collar. 1 it	t. 5.5"	
 6. Cement Specialist LLC, RU x Pump at 2 BPM, Lead – 187 Bbls,11.6# 50/50-H, and Tail-27 Bbls,12.0#, 65/35-H Cmt. x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWW A AUXILITIPLE President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Mark TITLE DATE DATE 	5.	CSG x Total lengt	h of 10,205' of 5.5", 1	17#, N-80, 8rd	l, LTC Casing (Top	of 5" Liner back	to Surface) inside of t	:he	
x Circulate 15 lbs. to Surface. 7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWWW AUMACTIFILE President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Maande TITLE DATE							07 DI 1 10 0/ (5/05)		
7. Sit down on the Liner Top with 40,000 lbs. weight x Set Slips x RDMO Pulling Unit x Wait on Cmt. to Setup. Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE WWWW AUTOL/LIFILE President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer APPROVED BY: Marth	6.			2 BPM, Lead	-187 Bbls, 11.6# 50	J/50-H, and Tail-	27 Bols, 12.0 #, $65/35$ -J	H Cmt.	
Spud Date: 09-21-2015 Rig Release Date: 09-30-2015 I hereby certify that the information above is true and complete to the best of my knowledge and belief. Image: Complete to the best of my knowledge and belief. SIGNATURE Image: Complete to the best of my knowledge and belief. SIGNATURE Image: Complete to the best of my knowledge and belief. SIGNATURE Image: Complete to the best of my knowledge and belief. SIGNATURE Image: Complete to the best of my knowledge and belief. Type or print name Image: Complete to the best of my knowledge and belief. Type or print name Image: Complete to the best of my knowledge and belief. For State Use Only Image: Complete to the best of my knowledge and belief. APPROVED BY: Image: Complete to the best of my knowledge and belief.	7.			lbs. weight x S	Set Slips x RDMO I	Pulling Unit x W	ait on Cmt. to Setup.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE William J. Savage President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com Petroleum Engineer 06/03/2016 APPROVED BY: Mining		- , ,	1 /	U	•				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE William J. Savage President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com Petroleum Engineer 06/03/2016 APPROVED BY: Mining			1.5 D	a Delega De		0 20 2015			
SIGNATURE William J. Savage President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Ittle DATE	Spud Date:	09-21-20	15 K	lg Kelease Da	ale: 0	9-30-2015			
SIGNATURE William J. Savage President DATE 10/10/2015 Type or print name William J. Savage E-mail address: bsavage@amtexenergy.com_PHONE: (432) 686-0847 For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Ittle DATE									
Type or print name William J. Savage Understand Description For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Integration DATE	I hereby certify	that the information	above is true and com	plete to the b	est of my knowledg	e and belief.	A	· ·	
Type or print name William J. Savage Understand Description For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Integration DATE		· .	•	-					
Type or print name William J. Savage Understand Description For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Integration DATE	SIGNATIOE	Mulian	1) Drivace	rippi fe	President	DATE 10/1	0/2015		
For State Use Only Petroleum Engineer 06/03/2016 APPROVED BY: Image: Comparison of the second	SIGNATURE_		C UNE				<u>V VIV</u>		
APPROVED BY: Petroleum Engineer 06/03/2016 DATE									
APPROVED BY:	For State Use	Only		Petro	leum Engineer		06/03/2016		
	APPROVED F	BY: 192	auk T						
KZ XZ								1	
				•.				KZ	