Submit 1 Copy To Appropriate District Office	Appropriate District State of New Mexico		Form C-103		
<u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources		Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.		
<u>District II</u> – (575) 748-1283	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		30-025-42392		
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178			5. Indicate Type of Lease <u>STATE X</u> FEE		
1000 Rio Brazos Rd., Aztec, NM 87410					
<u>District IV</u> - (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505					
	CES AND REPORTS ON WELL	S	7. Lease Nar	ne or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSA DIFFERENT RESERVOIR. USE "APPLICA PROPOSALS.)	ALS TO DRILL OR TO DEEPEN OR PI	LUG BACK TO A			
	Well \square Other OCD – HOBBS		Encore M State		
	04/29/2016		8. Well Number 18		
2. Name of Operator			9. OGRID N	lumber	
Breitburn Operating LP	REC	EIVED 🗸	370080		
3. Address of Operator	-			ne or Wildcat:	
600 Travis Houston, Texas 77002-3	026		WC-025	G-04 S2237201;Devonian	
4. Well Location					
	m the South line and 2050 feet f	rom the Fast line			
Section 20	Township 22S	Range 37E		County Lea	
	11. Elevation (Show whether DI	R, RKB, RT, GR, etc.			
	3373' GR				
NOTICE OF INT	ppropriate Box to Indicate N		-	REPORT OF:	
ERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK					
				— — —	
	MULTIPLE COMPL	CASING/CEMEN	I JOB	\boxtimes	
				airen an di aarrant	
OTHER: 13. Describe proposed or comple	tad operations (Clearly state all	OTHER: Intern			
	k). SEE RULE 19.15.7.14 NMA				
04/09/- 04/10/2016: NU BOPE. 1130'. Drill 1130' to 1200'. TOP			igh. All tests g	good. TIH. Tag cement @	
04/10/-04/12/2016: TIH w/ 12 ¹ / TOOH with 12 ¹ /4" bit and drill st					
rigging down casing crew. Main				. Chedidie bottoms up white	
04/13/2016 – 04/14/2016: Pump Displace w/ 340 bbls water. Bum tool with rig pumps. Cement 2 nd s ga/sks. Drop closing plug. Displa surface. Full circulation through casing to 1500 for 30 minutes. Ge	ped plug. Held 5 minutes. Bled b stage as follows: Lead- Allied Hi ace w/230 bbls water. Bump plug job. WOC. TIH to DV tool. Tag	ack 1.5 bbls. Dropp igh-Yield Class C 25 g. Close tool. Held 5 g cement @ 3037'. I	ed bomb. Open 55 bbls, 607 sks minutes. Float Drill DV tool. T	ted Tool. Circulate through D s, 11.9 ppg., 2.35 yield, 13.03 t held. Circulate 1.5 bbls. to ag cement @ 4483'. Test	
04/03/2016	Rig Release	Date:			
L					
hereby certify that the information a	pove is true and complete to the l	pest of my knowledge	e and belief.		
Sheller	Doescher				
IGNATURE		TITLE:	Agent I	DATE: 04/28/2016	
ype or print name <u>Shelly Doescher</u>					
ype of print name <u>Shelly Doeschel</u> for State Use Only	E-man address. sherry doesd	<u>noi w yanoo.com</u> P	1101ve. 303-3	20-3062	
	Dat	roloum Engineer	•	06/10/2016	
PPROVED BY:	TITLE TEL	roleum Engineeı		DATE	
Conditions of Approval (if any):	<u>111LE</u>				
Lonomons of Approval (If any): 🖉					

KZ