OCD – HOBBS 06/06/2017 RECEIVED

PECOS DISTRICT SURFACE USE CONDITIONS OF APPROVAL

OPERATOR'S NAME:	McElvain Energy Inc.
LEASE NO.:	NMNM0245247
WELL NAME & NO .:	2H - EK 30 BS2 Federal Com
SURFACE HOLE FOOTAGE:	150'/S & 876'/E
BOTTOM HOLE FOOTAGE	230'/N & 1980'/E
LOCATION:	Section 30 T.18 S., R.34 E., NMPM
COUNTY:	Lea County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

General Provisions
Permit Expiration
Archaeology, Paleontology, and Historical Sites
Noxious Weeds
Special Requirements
Lesser Prairie-Chicken Timing Stipulations
Below Ground-level Abandoned Well Marker
Construction
Notification
Topsoil
Closed Loop System
Federal Mineral Material Pits
Well Pads
Roads
Road Section Diagram
Production (Post Drilling)
Well Structures & Facilities
Interim Reclamation
Final Abandonment & Reclamation

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

<u>Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken</u>: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Below Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

This authorization is subject to your Certificate of Participation and/or Certificate of Inclusion under the New Mexico Candidate Conservation Agreement. Because it involves surface disturbing activities covered under your Certificate, your Habitat Conservation Fund Account with the Center of Excellence for Hazardous Materials Management (CEHMM) will be debited according to Exhibit B Part 2 of the Certificate of Participation.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

É. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, crodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope: $\underline{400'} + 100' = 200'$ lead-off ditch interval $\underline{4\%}$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.



Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, <u>Shale Green</u> from the BLM Standard Environmental Color Chart (CC-001: June 2008).

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Below Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

nerator Certification Data Report

06/22/2017

NAME: Natalie Stallsworth		Signed on: 02/03/2017
Title: Regulatory Technician/Permit	ting Agent	
Street Address: PO Box 99		
City: Eastlake	State: CO	Zip: 80614
Phone: (303)857-9999		
Email address: natalie@permitco-u Field Representative	usa.com	OCD – HOBBS 06/06/2017 RECEIVED
Representative Name: Street Address:		REC.
City:	State:	Zip:
Phone:		
Email address:		



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Application Data Report 06/22/2017

100

APD ID: 10400009238

Operator Name: MCELVAIN ENERGY INC

Well Name: EK 30 BS2 FEDERAL COM

Well Type: OIL WELL

Submission Date: 02/03/2017

1 1 1 2 2 2 1 1 2

Zlp: 80265

Well Number: 2H Well Work Type: Drill

	Section 1 - Genera			
APD ID:	10400009238	Tie to previous	NOS? S	ubmission Date: 02/03/2017
BLM Offic	e: CARLSBAD	User: Natalie S	alisworth Title: R	egulatory
Federal/In	idian APD: FED	is the first leas	Technic e penetrated for production l	ian/Permitting Agent Federal or Indian? FED
Lease nur	nber: NMNM0245247	Lease Acres: 1	111.44	
Surface a	ccess agreement in plac	s? Allotted?	Reservation:	
Agreemer	nt in place? NO	Federal or Indi	an agreement:	
Agreemen	nt number:			
Agreemen	nt name:			
Кеер арр	lication confidential? YE	s		
Permitting	Agent? YES	APD Operator:	MCELVAIN ENERGY INC	
Operator	letter of designation:	Agent Letter signed_12-1	6-2016.PDF	
Keep appl	lication confidential? YE	s		
	Operator Info			

Operator Organization Name: MCELVAIN ENERGY INC Operator Address: 1050 17th St #2500 Operator PO Box: Operator City: Denver State: CO Operator Phone: (303)893-0933

Operator Internet Address: chris.caplis@mcelvain.com

Section 2 - Well Information

Well in Master Development Plan? NO	Mater Development Plan nam	e:
Well in Master SUPO? NEW	Master SUPO name: EK 30 an	d 31 Multi-pad
Well in Master Drilling Plan? NO	Master Drilling Plan name:	
Well Name: EK 30 BS2 FEDERAL COM	Well Number: 2H	Well API Number:
Field/Pool or Exploratory? Field and Pool	Field Name: BONE SPRING	Pool Name:

Operator	Name:	MCEL	VAIN	ENERG	Y INC
Well Nam	e: EK 3	0 BS2	FEDE	ERAL C	OM

Well Number: 2H

is the proposed w	ell in an area containing other r	mineral resources? USEABLE WATE	R
Describe other mi	inerals:		
Is the proposed w	vell in a Helium production area	? N Use Existing Well Pad? NO	New surface disturbance?
Type of Well Pad:	SINGLE WELL	Multiple Well Pad Name:	Number:
Well Class: HORI	ZONTAL	Number of Legs:	
Well Work Type:	Drill		
Well Type: OIL W	ELL		
Describe Well Ty	96:		
Well sub-Type: E	XPLORATORY (WILDCAT)		
Describe sub-type	a:		
Distance to town:	28 Miles Distance 1	o nearest well: 30 FT Distan	ce to lease line: 150 FT
Reservoir well sp	acing assigned acres Measuren	nent: 160 Acres	
Well plat: EK 3	0 BS2 Federal COM 2H Plat_02-	01-2017.pdf	
Well work start D	ate: 09/28/2017	Duration: 35 DAYS	
Section 3	- Well Location Table		
Survey Type: REC	TANGULAR		
Describe Survey	Гуре:		
Datum: NAD83		Vertical Datum: NAVD88	
Survey number:			
	STATE: NEW MEXICO	Meridian: NEW MEXICO PRINCIPAL	County: LEA
	Latitude: 32.7118722	Longitude: -103.5938972	
SHL	Elevation: 3894	MD: 0	TVD: 0
Leg #; 1	Lease Type: FEDERAL	Lease #: NMNM0245247	
	NS-Foot: 150	NS Indicator: FSL	
	EW-Foot: 876	EW Indicator: FEL	
	Twsp: 18S	Range: 34E	Section: 30
	Aliquot: SESE	Lot:	Tract:

Operator Name: MCELVAIN ENERGY INC Well Name: EK 30 BS2 FEDERAL COM

Well Number: 2H

	STATE: NEW MEXICO	Meridian: NEW MEXICO PRINCIPAL	County: LEA
	Latitude: 32.7114664	Longitude: -103.5973619	
KOP	Elevation: -5565	MD: 9542	TVD: 9459
Leg #: 1	Lease Type: FEDERAL	Lease #: NMNM0245247	
	NS-Foot: 50	NS Indicator: FSL	
	EW-Foot: 1976	EW Indicator: FEL	
	Twsp: <mark>18</mark> S	Range: 34E	Section: 30
	Aliquot: SESE	Lot:	Tract:
	STATE: NEW MEXICO	Meridian: NEW MEXICO PRINCIPAL	County: LEA
	Latitude: 32.7150889	Longitude: -103.5974028	
PPP	Elevation: -5999	MD: 11450	TVD: 9893
Leg #: 1	Lease Type: FEDERAL	Lease #: NMNM116166	
	NS-Foot: 1320	NS Indicator: FSL	
	EW-Foot: <mark>1950</mark>	EW Indicator: FEL	
	Twsp: 18S	Range: 34E	Section: 30
	A HE A HARMAN A	And the second	Warren for
	Afiquot: NWSW	Lot:	Ifact:
	STATE: NEW MEXICO	Lot: Meridian: NEW MEXICO PRINCIPAL	County: LEA
	STATE: NEW MEXICO	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972	. County: LEA
PPP	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400	TVD: 9933
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247	TVD: 9933
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL	TVD: 9933
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL	TVD: 9933
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E	TVD: 9933 Section: 30
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E Lot:	TVD: 9933 Section: 30 Tract:
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE STATE: NEW MEXICO	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E Lot: Meridian: NEW MEXICO PRINCIPAL	TVD: 9933 Section: 30 Tract: . County: LEA
PPP Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE STATE: NEW MEXICO Latitude: 32.7250667	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FSL EW Indicator: FEL Range: 34E Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5974278	TVD: 9933 Section: 30 Tract: County: LEA
PPP Leg #: 1 EXIT	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE STATE: NEW MEXICO Latitude: 32.7250667 Elevation: -5883	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5974278 MD: 14765	TVD: 9933 Section: 30 Tract: County: LEA TVD: 9777
PPP Leg #: 1 EXIT Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE STATE: NEW MEXICO Latitude: 32.7250667 Elevation: -5883 Lease Type: FEDERAL	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5974278 MD: 14765 Lease #: NMNM116166	TVD: 9933 Section: 30 Tract: County: LEA TVD: 9777
PPP Leg #: 1 EXIT Leg #: 1	Afiquot: NWSW STATE: NEW MEXICO Latitude: 32.7118722 Elevation: -6039 Lease Type: FEDERAL NS-Foot: 583 EW-Foot: 1951 Twsp: 18S Aliquot: SWSE STATE: NEW MEXICO Latitude: 32.7250667 Elevation: -5883 Lease Type: FEDERAL NS-Foot: 330	Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5938972 MD: 10400 Lease #: NMNM0245247 NS Indicator: FSL EW Indicator: FEL Range: 34E Lot: Meridian: NEW MEXICO PRINCIPAL Longitude: -103.5974278 MD: 14765 Lease #: NMNM116166 NS Indicator: FNL	TVD: 9933 Section: 30 Tract: County: LEA TVD: 9777

Operator Name: MCELVAIN ENERGY INC Well Name: EK 30 BS2 FEDERAL COM

Well Number: 2H

	Twsp: <mark>18S</mark>	Range: 34E	Section: 30
	Aliquot: NWNE	Lot:	Tract:
	STATE: NEW MEXICO	Meridian: NEW MEXICO PRINCI	PAL County: LEA
	Latitude: 32.7253389	Longitude: -103.5975333	
HL	Elevation: -5880	MD: 14862	TVD: 9774
.eg #: 1	Lease Type: FEDERAL	Lease #: NMNM116166	
	NS-Foot: 230	NS Indicator: FNL	
	EW-Foot: 1980	EW Indicator: FEL	
	Twsp: 188	Range: 34E	Section: 30
	Aliquot: NWNE	Lot:	Tract:



MCELVAIN ENERGY, INC. 1050 17th Street, Suite 2500 Denver, Colorado 80265

CHRIS CAPLIS VICE PRESIDENT OF DRILLING AND COMPLETION OFFICE: 303-962-6475 FAX: 303-893-0914 E-MAIL: CHRIS.CAPLIS@MCELVAIN.COM

Bureau of Land Management Carlsbad Field Office 620 E. Greene St. Carlsbad, NM 88220

Attn: Minerals Divison

Re: All McElvain Energy Inc. wells in New Mexico

Gentlemen:

This letter is to inform you that Permitco Inc. is authorized to act as Agent and to sign documents on behalf of McElvain Energy Inc. when necessary for filing county, state and federal permits including Onshore Order No. 1, Right of Way applications, etc., for the above mentioned well.

It should be understood that Permitco is acting as Agent only in those matters stated above and is not responsible for drilling, completion, production or compliance with regulations.

McElvain Energy Inc. agrees to accept full responsibility for operations conducted in order to drill, complete and produce the above-mentioned well.

Sincerely,

Chris Caplis MCELVAIN ENERGY, INC. 1050 17TH STREET, SUITE 2500 DENVER, COLORADO 80265