

Well Name: LAKEWOOD 28 FED COM

Well Location: T25S / R34E / SEC 28 / SESE / 32.0947913 / -103.468018

County or Parish/State: LEA / NM

Well Number: 702H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM94115

Unit or CA Name:

Unit or CA Number:

US Well Number: 300254684800X1

Well Status: Drilling Well

Operator: EOG RESOURCES INCORPORATED

Notification

Type of Submission:

Notification

Type of Action:

Casing and Cementing

Date Sundry Submitted:

Mar 17, 2021

Time Sundry Submitted:

8:24:53 AM

Date Operation will begin:

Nov 17, 2020

Time Operation will begin:

11:00:00 AM

Field Contact Name:

C FELTS

Field Contact Number:

4326363600

Rig Name:

Rig Number:

HP462

Well Casing Table:

String Type	Top Setting Depth MD	Top Setting Depth TVD	Top Setting Depth MSL	Bottom Setting Depth MD	Bottom Setting Depth TVD	Bottom Setting Depth MSL
PRODUCTION	11555	11555	-8232	22833	12625	-9303
PRODUCTION	0	0	3323	11055	11055	-7732
SURFACE	0	0	3323	870	870	2453
INTERMEDIATE	0	0	3323	11555	11555	-8232
PRODUCTION	11055	11055	-7732	11555	11555	-8232

**Procedure Description:**

11-18-2020 12 1/4" HOLE  
11-18-2020 Surface Hole @ 1,019' MD, 1,019' TVD  
Casing shoe @ 1,004' MD  
Ran 9-5/8" 40# J-55 LTC  
Cement w/ 425 sx Class C (1.60 yld, 13.8 ppg), Trail w/115 sx Class C (1.33 yld, 14.8 ppg)  
Test casing to 1,500 psi for 30 min - Good. Circ 144 sx cement to surface

11-23-2020 8 3/4" hole  
11-23-2020 Intermediate Hole @ 11,985' MD, 11,956' TVD  
Casing shoe @ 11,970' MD  
Ran 7-5/8", 29.7#, HCP-110 MO-FXL  
Stage 1: Cement w/ 430 sx Class H (1.19 yld, 15.6 ppg)  
Test casing to 2,700 psi for 30 min - Good. Did not circ cement to surface, TOC @ 7,000' by Calc  
Stage 2: Bradenhead squeeze w/ 1,000 sx Class C (1.52 yld, 14.8 ppg)  
Stage 3: Top out w/ 107 sx Class C (1.36 yld, 14.8 ppg), Lines flushed w/ 4 bbls FW, TOC @ 25' by Echometer

12/4/2020 6-3/4" Hole  
12/4/2020 Production Hole @ 22,779' MD, 12,577' TVD  
Casing shoe @ 22,779' MD, 12,577' TVD  
Ran 5-1/2", 20#, ICYP-110 DWC (0' - 11,311') (MJ @ 12,119' and 22,230')  
Ran 5-1/2", 20#, ICYP-110 TLW-SC (11,311' - 12,119')  
Ran 5-1/2", 20#, ICYP-110 DWC (12,119' - 22,779')  
Cement w/ 1,095 sx Class H (1.19 yld, 14.5 ppg)  
Test casing to 5,970 psi for 10 min - Good. Did not circ cement to surface, TOC @ 9,300' by CBL RR 12/5/2020

<b>Well Name:</b> LAKEWOOD 28 FED COM	<b>Well Location:</b> T25S / R34E / SEC 28 / SESE / 32.0947913 / -103.468018	<b>County or Parish/State:</b> LEA / NM
<b>Well Number:</b> 702H	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM94115	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 300254684800X1	<b>Well Status:</b> Drilling Well	<b>Operator:</b> EOG RESOURCES INCORPORATED

<b>Disposition:</b>	Accepted
<b>Accepted Date:</b>	05/18/2021