

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-07628
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name McKinley
Well No. 19
Pool name or Wildcat Bowers; Seven Rivers

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:
OIL WELL GAS WELL OTHER TA'D

Name of Operator
Occidental Permian LTD

Address of Operator
1017 W. Stanolind Rd. Hobbs, New Mexico

Well Location
Unit Letter E : 1650 Feet From The North Line and 660 Feet From The West Line
Section 5 Township 19 S Range 38 E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ANBANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3244' 9 5/8" @ 453' Circ. 5 1/2" 3160' TOC @ 425' OH 3160'-3244' CIBP @ 3080'
5-5-03 Tag Existing CIBP @ 3080' Circ. well w/ M.L.F. Spot 25 sks of cement 3080'-2833' Spot 25 sks of cement 2705'-2458'
Spot 25 sks of cement 1612'-1365'
5-6-03 Perf @ 425' Circ. 130 sks of cement down 5 1/2 up annulus to surface.
Cut off wellhead and anchors 4' BGL. Cap well. Install dry hole marker, 4' under ground.

Approved as to plugging of the Well Bore.
Liability under bond is retained until surface restoration is completed.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SR Engr Tech DATE 5-6-03
TYPE OR PRINT NAME Robert Gilbert TELEPHONE NO. 397-8206

(This space for State Use)

APPROVED BY Hayward W. Winkler OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE MAY 21 2003
CONDITIONS OF APPROVAL, IF ANY: